

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ 8	T. _____ 2 S., R. _____ 2 E.	D-4, D-5
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

Donald L. Bissell

I, _____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-4 Center section	D-4 S $\frac{1}{4}$ Corner
Set at intersection of N-S & E-W $\frac{1}{4}$ lines	Found old fence corner post surrounded by stones. Checked Government distances from East & West. Accepted as best evidence.
4" x 36" Conc. mon. with aluminum cap.	Set 4" x 36" Conc. mon. w/aluminum cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-4 4" x 36" Conc. mon. w/alum. cap.	D-4 4" x 36" Conc. mon. w/aluminum cap
N15°W - 5.52' - 4" Hickory	S3°E - 29.70' - 15" Oak
S42°W - 15.58' - 7" Hickory	N51°W - 9.85' - 4" Hickory
S2°E - 19.31' - 5" W. Oak	N8°E - 26.02' - 24" W. Oak
N81°E - 15.33' - Fence Cor. post.	N73°E - 8.00' - 20" B. Oak


SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L. Bissell CHIEF OF SURVEY PARTY DATE 10-18-83
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. 18655