						•
APPROVED P.A. 3	ON COUNTY LAND CORNEY 45 of 1990	West ‡ P Parma To	•	TION 12		. ઉપલબ્ધા હોત્ર ફ્રાંડિકો
Acrine Chairman Timera Data	MARCH 12, 1997			TION CERTIFICAT 74, Mich. P.A. 197		#2029641 Liber 1538 Page 50 Fage 1 of 2
For corners in JACKS0		Located in:	Corner Co			Jackson Co., MI Recorded
(Co	ounly)			ue ++		03/13/9 7 03:40P Minda Reilla
Public Lan	d Survey	T 2 S R 3 W T R	K-4			Register of Deeds
2. Property C	Controlling S	T R T RRI _ T R	SURVE IBMUNOME	Y-& VTATION		
in Section 3. Miscellane Property in	S sous	T R T R T R	APR 0 7	1992	egister of Deeds	Stamp & File Number
4. Lot No	Recorded	l Plat	SECTIO	N		•
	ims				- A B C D	E F G H I J K L
					3	
Dean R. G	utekunst , in a lie	ld survey on6/27/	'96 & 7/18	96	5	9-10-11-0-12
do hereby certify	that under requirement	s of P.A. 74, Michigan P.A. ance with regulations and	of 1970, the corner	pointsmentioned	6 18 17	16 15 14 13
		the United States Depart Law and/or that the corner		•	7 30 20	21 22 23 24
		s of the Michigan Board of shed, monumented, re-m	•		9 1 1	
expressed below		ill in the same town an	d range may be	recorded	10 30 29	28 27 26 25
	certificate.	m the same town an	a lenge, may be	, recorded	12 31 32	33 34 35 36
Origina B. O	al Government P ak 19" S 8	ant and accessories and cost set by Lucius $1\frac{1}{2}$ W 27 link 8 E 48 link	s Lyon, Der		April 1825.	
	_	for the 1880's.			a	
South	hwest corner of	, # 377, no date Church step cem School house st	ent - NE	- 104.4° - 74.5°	Set ir Road s	on pipe in urvey.
	ued on back,		P 1			
Found a		ound and/or method append box with a $\frac{1}{2}$ Road.				surface of
		a 6' North & So evidence of the			y 7' deep ar	ea did not
		s a careful and monumented by Ri		rpetuation of	the position	n of the
Set a S	Standard Jackso	n County Monumen	t to replac	e iron and bur	ried irons b	eside monument.
C. Description K-4	of monument for corr	ner and accessories es Corner is a 4" (_
V	125, RJ#	steel rod and as	n aluminum	cap stamped LS		
	55° E 30" 1	hwest corner sto Maple 56		on of church	108.41' North side.	DEAN
	350 W 6"1		.3 ce	nter line. no	nail.	
		Maple	76.69	40d & washer 40d & washer ounty Road Com	on South sid	e III
Мо	onument box set	over monument by	y Jackson C			farch 1, 1997
Signed by	Slan Ky	18658		Date		
Surveyor's Michi	igan License No			FORM APPRO	YED SY MICHIGAN STATE BI)ARD OF LAND SURVEYORS, JAN 28, 197 REVISED MAY 14, 197

#2029641 Pa 2 of 2

K-4 T2S, R3W

Δ

- Perpetuation by Richard E. Gutekunst, RIS # 7863, dated 10/4/1967.

NE to SWC church 108.45' Found iron
NW to SEC school 76.85'

* S 50 E 20" Maple 55.90'

** S 60 W 20" Walnut 90.40'

- Perpetuation by Richard E. Gutekunst, RIS # 7863, dated 2/8/1974

Found iron 3" below blacktop surface

* S 45 E 24" Maple 56.75'

*** N 60 E SWC church foundation 108.4'

N 45 W SEC house foundation (addition) 72.75'

** S 60 W 20" Walnut 91.5'

- P.A. 74, recorded by Richard E. Gutekunst, RLS # 7863, dated February 13, 1976, in ICRC, Liber 2, Page 601, Jackson County Records.

Same information as above, 2/8/1974.