Surveyor's Michigan License No. 24621

JACKSON LOCK III	
P.A. 349 of 1999 . CENTER 1/4 POST	CPOTTON 21
CIRCLE MOUNT	
CHARLES TOTAL	
Date 11-24-99 LAND CORNER RECORDA	
For corners in	
Jackson Located In: Corner	Code # MAR 1 3 2000
(County)	
2 d 1 m	. SECTION
1. Public Land Survey T 3 S R 1 W B-1	2
T R T R	
T R	Page: 1 of 2 12/28/1999 11:41A
2. Property Controlling S T R	
in Section S T R Mindy R	eilly - Jackson Co. CORREM
3. Miscellaneous S T B	Register of Deeds Stamp & File Number
Property in Section S T R	nagister of peeds stainly & File Natither
4. Lot No, Recorded Plat	
5. Private Claims	A B C D E F G H I J K L
	2 - 6 5 3 2 1 -
Training the n	3
Timothy B. VanGieson April 21	4 7 4 9 4 10 - 11 1 - 12
VanGieson in a field survey on April 21 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the co	19 90 ,
in lines 1 and 2 above were in conformance with regulations and rules therefore as	required in the current
manual of survey instructions of the United States Department of the Inte	rior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points ment 5 above were in conformance with the rules of the Michigan Board of Profession	loned in lines 3, 4 and 8 19 20 21 22 23 24 24 24 24 24 25 24 25 24 25 24 25 24 25 25 24 25 25 25 25 25 25 25 25 25 25 25 25 25
Decree of a Court of Law; established, re-established, monumented, re-monumer	nted, recovered, found
as expressed below:	10 30 29 28 27 26 25
NOTE: Not more than 4 corners, all in the same town and range, may be on this certificate.	recorded 12 3 34 34 35 36
On this definicate.	13 7 7 7 7
B-12: Corner established in a boundary survey date Registered Land Surveyor No.24621. "3/4" x 24" Pipe Corner established by intersection of 1/4 list South 1/4 Post 3/4" pipe North 1/4 Post Fire Clay West 1/4 Post 3/4" Crimp-Pipe East 1/4 Post 3/4" Pipe B-12: See back for additional supporting documents B. Description of corner evidence found and/or method applied in res B-12: In a boundary survey that I performed on Apr found to be 0.14' North, 0.19' West, of interemonumented positions. Corner falls at Nor Accepted pipe as faithful and careful perpet in 1979. Set standard Jackson County Remonumentation pipe.	ines based on found monumentation described as ation. Ition. Itiong or reestablishing corner: II 21, 1998, this point was recovered and exsection of 1/4 lines based on current oth edge of asphalt on Sears Road. Itiuation of center 1/4 Post as monumented
C. Description of monument for corner and accessories established to B-12: 4" x 30" Harrison Monument with brass cap R. N 00° E Sign post N 04° E 60-d in East side 24" Hickory N 53° E 60-d in Northwest side 14" Oak N 73° E 60-d in North side 11" Cherry N 79° E 60-d in North side 22" Oak S 56° E 60-d in Northeast side 12" Cherry S 02° E 60-d in East side of 10" Hickory	
Signed by Timothy B. VanGieson	Date November 22, 1999

SURVEY & REMONUMENTATION

A (continued)

Source: Timothy B. VanGieson Registered Land Surveyor No.24621

Date: September 25, 1979

3/4" x 24" Pipe

20 nail in 24" Hickory N 00° E 24.64'

20 nail in twin 8" Cherry N 70° E 44.23'

20 nail in 10" Cherry S 70° E 105.51'

20 nail in 6" Hickory S 30° W 63.82'

MAR 1 3 2000

SECTION

Page: 2 of 2 12/08/1999 11:41A L-1618 P-1230