87

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N. S., R. 6 E. W.	C-7; B-7; A-7; A-6
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 23, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

A-7

Fd. D.N.R. Mon.; added ced. post

*20" R. Pine	S85°W	23.1
*20" R. Pine	S20°E	13.8
4" Maple	N37°E	17.5

* = Old Wits

A-6

Fd. 1" pipe (Fargo) & added D.N.R. Mon. & ced. post

10" Cedar	N64°W	24.6
16" Maple	N08°E	43.2
8" Cedar	N86°E	55.4

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-7 Fd. 1" pipe in ctr. of N-S gravel road. No remaining evidence of Fargo (1912) iron or witnesses but corner fits Fargo data reasonable.

B-7 Fd. Dept. Monument (M. Schaaf 1940-K. Ostling 1956) with Fargo 1" pipe (1912) along side same. Good original Govt. corner.

A-7 Fd. Dept. Monument (M. Schaaf 1940-K. Ostling 1956) with Fargo 1" pipe (1912) along side same. Good original Govt. corner.

A-6 Recovered & accepted Fargo 1" pipe. They fd. a stake here in 1912.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7

Fd. 1" pipe (buried); raised w/1" pipe

*12" J. Pine	N64°E	68.0
* 8" Cherry	N57°W	72.5
Power Pole	N84°W	30.94
11" Cherry (cluster)	N29°W	113.6
Ced. Post w/tag	W	32.5

* = Old Wits.

B-7

Fd. D.N.R. Mon.; added cedar post

*13" dead J. Pine	S73°E	103.5
13" Cherry	S46°W	48.8
8" Cherry	S25°E	79.5

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

SIGNED BY Carl F. Roser 3-16-81 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

GARFIELD TOWNSHIP (Central Part)
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET