

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>26</u> N. <u>●</u> , R. <u>5</u> W. <u>●</u>	<u>H-1; H-2</u>
2. PROPERTY CONTROLLING IN SECTION <u>3</u>	, T. <u>26</u> N. <u>●</u> , R. <u>5</u> W. <u>●</u>	<u>11; 12</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. _____, R. _____ E. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 7, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. - Description of original monument and accessories and/or subsequent restoration:~~

C. (continued)

12

Set 5/8" Rod w/RLS Cap &
Cedar Post

3" W. Pine	N65°E	24.82
3" W. Pine	S58°E	22.53

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Reset corner by proportionate measurement between section corners. Falls about 2' NE of Houghton position and 12'± east of Schaaf position.

1-1