LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 8 E. W.	H-1,I-2,I-3,
2. PROPERTY CONTROLLING IN SECTION 3	,T. 26 N. S., R. 8 E. W.	7
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 5-3-78, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument and accessories and/or subsequent restoration:~~

7

Set 5/8"X40" re-rod w/RLS Cap &
ced.Post w/Loc. Tag.

14"W.Pine	N88°W	27.2
10" Maple	N21°W	14.8
9" R.Pine	S40°E	26.5

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H-1 Re-established 1/4 corner equidistant & on line between sec. corners to E&W.

I-2 Fd. 5/8" re-rod with RLS cap, Verba, #13603, as a restored 1/4 cor. pro-rated to U.S.

I-3 Found 1 1/2" dia. round iron pin, buried 0.5' in Southly wheel track of E-W trail road.

7 Established 1/8 corner on line between Sec. cor. N. & 1/4 cor. S. and at pro-rated distance to G.L.O. survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-1

Set DNR Mon. & Ced.Post

9" R.Pine	N17°E	27.6
11" R.Pine	S77°E	56.2
4" Maple	S38°W	6.2

I-2

Fd. 5/8" re-rod & Set Ced.Post w/Loc. Tag

5" Maple Cluster of 6

	S02°W	31.08
6" Cherry	S53°W	23.6
10" Oak	N36°W	14.6
4" Maple	N14°E	22.5
10" Cherry	N44°E	32.49
N-S random	Due E	1.55'

I-3

Fd. 1 1/2"X1.5' Iron pin
Ctr.3" Pipe-Mi.Con Gas Pipe
line marker S71°E 245.8
Set Ced.Post w/Loc. tag
Due N 33'
Map clump
(Verba-#13603) S82°E 68.58
9" Pin Cherry(Verba)
S65°W 34.24
Irreg. Trail rd-N'ly.
Due E 25'±

SIGNED BY Carl F. Roser 9-18-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
SEAL
REGISTERED LAND SURVEYOR

BOARDMAN TOWNSHIP
KALKASKA COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET