## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN -:	CORNER COL	E NUMBER		
	1. PUBLIC LAND SURVEY	T. 26 N., R. 8		-6		•
	2. PROPERTY CONTROLL- ING IN SECTION—	16 ,T. 26 N., R. 8	_ w. 8; 9			
	3. MISCELLANEOUS PROPERTY IN SECTION —	,T N	E. W.			
	4. LOT NO , R	ECORDED PLAT				•
	5. PRIVATE CLAIMS			RE	GISTER OF DEEDS FILING NUM	
	I, <u>Carl F. Roser</u> the corner points mentioned is re-established, monumented, and rules therefore as require. Bureau of Land Management and 5 above were, in a field so as expressed below and in confidence of a Court of law:	re-monumented, recovered ed in the current manual of or by a decree of a court of urvey on	, in a field survey on_ or restored as expres survey instructions of f law. Furthermore, t , 19, found,	April 10 sed below and in the United States that the corner po recovered, restored	, 1978 conformance with a Department of ints mentioned l, established or	, 'established, h regulations the Interior, in lines 3, 4 re-established
	KK KKKKEXKIK KKKKKKK X X X	ÓK KATKOPKASKA BAKA KOMBUKK	KAKAK KHEKIREKHIK KOND	MMMXX		
E-6 E-7 F-6 8	In Old Fn. So B. Description of corner evic Fd. 1/2" rod, burie fence to W. Previo Fd. Ir. with RLS Ca Fd. rod with RLS Ca Perla-Stout, L.Czub Established 1/8 Cor Established 1/8 Cor	NO5°E 42.45 S52°E 57.24 S65°W 51.62 od 9-50E 13.34 uth (down) + dence found and/or method d, in approx. ctr. us Dept. Cor. of rep in Ctr. E-W black p, at intersection eek, RLS. Cor. is interper Std. B.L.M. mer per Std. B.L.M.	Post w/L 3" W. Pi 8" W.Pin 7" W.Pin I applied in restoring of of N-S gravel cecord (1967). I top road, grav of onequarter 1 in line with ctr instructions. instructions.	ne SOS°E e S27°W e N42°W  or re-establishing co- county road, ines, for Ctr e. of gravel r	64.1 52.8 28.9 orner: n line with S. c. of Sec. 10	6. Rod b
3/4' 14'' 21'' 17''	C. Description of monument E-6 1/2" rod; raised with "X18" pipe. W.Pine S44°E 38. W.Pine N25°E 84. R.Pine N37°W 58. Cedar Post w/Loc. Tag 33'	Fd. RLS Cap is could not real could	E-7 In B.Top rd., Id number. S12°E 63.06 J24°E 107.43	Fd. 1/2" Ro Fd. 1/2" Ir 26" Ir. Woo 30" Maple 23" Maple	F-6 d w/Cap . Rod Buried Do≨'S d S47°W	1 <i>0.5′~</i> 27.11 64.49 22.27
	SIGNED BY		9-18-78	July 12	OF MICH	27.4
				DATE	CARL 7	
	SURVEYOR'S MICHIGAN	REGISTRATION NO	12028		LANDEAL)	
	FOR STATE AND UNITE	STATES AGENCIES:			No. 12028	
	SIGNED BY	CHIEF OF SURVEY PARTY		DATE.	O LAND SURVINIO	
	APPROVED AND SIGNED		ERED LAND SURVEYOR	DATE	(SEAL)	
•	CURVENOR'S MICHICAN	DECOME TO SECOND			N TOWNSHIP	

E-6

The second secon