LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 26 N. S., R. 8 E. W.	H-5; H-7; I-7
2. PROPERTY CONTROLLING IN SECTION 15	T. 26 N. S., R. 8 E. W.	2
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 3, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued) 2

Set 5/8"X3' Re-Rod w/Cap. &
Cedar post w/Loc. Tag

3" Maple	S23°E	15.95
7" Maple	S68°W	45.86
7" W.Pine	N71°W	51.00
Ctr.Trail	Due N	30'±
Fd. 1/2" Re-rod w/Cap #19830 E		72.72

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H-5 Re-estab. 1/4 Cor. on line between Sec. Corners to E.&W. and at pro-rated distance to W.S. Merrill Survey of S. line Sec. 10, Book #23, Pg. 129, Feb. 1909.

H-7 Fd. & accepted PK nail in Ctr of E-W B.Top Co. road, in line with old fence remains to South. Fits Mosher Survey of 1888.

I-7 Fd. & accepted 1" shaft, buried 1.0 ft., in County Road intersection N-S-E-W.

2 Established 1/8 Corner per Std. B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-5

Set DNR Mon. & Ced.Post

10" Maple	N13°E	55.4
12" R.Pine	N88°W	37.0
9" Twin R.Pine	S05°W	49.5

H-7

Fd. PK & replaced with 5/8X18" Re-rod w/R.L.S. Cap Buried 0.2

Apple Tree	N12°W	73.15
Apple Tree	N60°W	89.56

I-7

Fd. 1" Shaft & raised with 1 1/4" pipe

W.Pine	N38°W	73.06
P.Pole	N30°E	75.35

SIGNED BY Carl F. Roser DATE 9-18-78

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

BOARDMAN TOWNSHIP
KALKASKA COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET