LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 8 E. W.	E-4 E-5 F-5
2. PROPERTY CONTROLLING IN SECTION 9	,T. 26 N. S., R. 8 E. W.	3; 15
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 17, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~Description of original monument and accessories and/or subsequent restoration~~

C. (continued)

3

Set 5/8"X40" re-rod w/R.L.S. Cap & Ced.Post w/Loc. Tag.

7" Maple	N18°W	50.9
11" Cedar	S76°W	27.1
12" Cedar	S07°W	33.3

15

Set 3/4"X5' re-rod w/Cap & Ced.Post w/Loc. Tag.

6" Oak	S73°W	8.6
12" W.Pine	N45°W	75.3
15" W.Pine	S64°E	31.8
3/4" Pipe (flush w/ground)		
	N50°E	37.16
Ctr.E-W Tr. Rd. N		22'±

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-4 Fd. Dept. Mon. as estab. in 1967 (Proportionate Mea. between Sec. Cor's N&S) to be four feet to far south. Re-estab. 1/4 Cor. at pro-rated distance to W.S.Merrill Survey of West line of Sec.9, dated Oct.21,1908. Moved existing Dept. Mon.4.4'-N & 1.4'-W. and re-wit.

E-5 Up-graded previous Dept. Cor. of Record, 1967.

F-5 Fd. 1/2" re-rod, R.L.S. L. Czubak, who re-established 1/4 Cor. by single proportion.

3 Established 1/8 Corner per Std. B.L.M. instructions.

15 Established 1/8 Corner per Std. B.L.M. instructions. Old fence remains to west are 3'± South.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-4

Re-set Exist. Dept. Mon. & Set Ced.Post

7" R.Pine	S50°E	11.2
12" R.Pine	S25°W	35.5
14" Oak	N01°E	63.7
17" Y.Pine Stp.	N40°E	1.5

E-5

Fd. Dept. Mon. & added Ced.Post

3" W. Pine	N23°W	50.23
4" Maple (cluster of 3)		
	N 21°E	35.39
5" W.Pine	S12°E	49.20
Ctr. of Tr. Rd. E&W	N	5'±
Ctr of Graded Rd. N&S		
	W	50'

F-5

Fd. R.L.S. re-rod #12581 added D.N.R. mon. & Ced.Post

12" W.Pine	N67°E	18.75
5" Maple	S34°E	34.15
10" Balsam	S19°W	10.45
4" Maple (cluster of 3)		
	N74°W	32.50
Ctr. of E-W Tr. Rd.		
	Due N	25'±

SIGNED BY Carl F. Roser 9-18-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BOARDMAN TOWNSHIP
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET