LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER		
	1. PUBLIC LAND SURVEY	T26N8	H-5; H-7; I-7	_	
	2. PROPERTY CONTROLL-] ING IN SECTION——	5 ,T. 26 N. R. 8 W.	2	_	
	3. MISCELLANEOUS PROPERTY IN SECTION	N. R. E. W. W.		_	
	4. LOT NO, RECORDED PLAT				
	5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER	
	the corner points mentioned in re-established, monumented, r and rules therefore as required Bureau of Land Management and 5 above were, in a field su as expressed below and in con	the corner points mentioned in lines 1 and 2 above were, in a field survey on May 3, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, rureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on			
	Decree of a Court of law: XX XIXXX XXXXXXXXXXXXXXXXXXXXXXXXXXXX				
H-5 H-7 I-7	Set 5/8"X3' Re-Rod w/Cap. & Cedar post w/Loc. Tag 3" Maple S23°E 15.95 7" Maple S68°W 45.86 7" W.Pine N71°W 51.00 Ctr.Trail Due N 30'+ Fd. 1/2" Re-rod w/Cap #19830 E 72.72 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: Re-estab. 1/4 Cor. on line between Sec. Corners to E.&W. and at pro-rated distance to W.S. Merrill Survey of S. line Sec. 10, Book #23, Pg. 129, Feb. 1909. Fd. & accepted PK nail in Ctr of E-W B.Top Co. road, in line with old fence remains to South. Fits Mosher Survey of 1888. Fd. & accepted 1" shaft, buried 1.0 ft., in County Road intersection N-S-E-W.				
2	Established 1/8 Corner per Std. B.L.M. instructions. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:				
10'' 12''		Re-rod w/R.L.S. (Apple Tree N6 Apple Tree N6	Cap Buried 0.2 1 2°W 73.15 W	I-7 d. 1" Shaft & raised with l/4" pipe Pine N38°W 73.06 Pole N30°E 75.35	
	SURVEYOR'S MICHIGAN F FOR STATE AND UNITED SIGNED BY		DATE	CARL' F. ROSER LAND NO. 12028	
•	CUDVEVOR'S MICHICAN I	ATIONOTE ATION NO		ARDMAN TOWNSHIP LKASKA COUNTY	

H-5

H-7

Set