LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 8 E. W.	F-7; G-6; G-7
2. PROPERTY CONTROLLING IN SECTION 16	,T. 26 N. S., R. 8 E. W.	12
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 12, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. (continued) 12

Fd. 1/2" Rod w/Cap (buried 0.2')		
Ctr. U.S. 131 in Curve	S.	38.0
P.Pole	N34°W	71.58
16" Maple	N12°W	92.90
Fd. 1/2" Re-rod w/Cap	N.	76.82
Hwy. R/W Marker	N27°E	107.2

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

F-7 Found 1 1/4" pipe (buried) in line with approx. ctr. of B.Top road to North and 11'± South of Ctr. of E-W B.Top road. Fits previous survey by Moser (1883) & recent survey in Sec.16 by Perla & Stout, L. Czubek, RLS.

G-6 Fd. & accepted re-rod with RLS Cap #12581, L. Czubek.

G-7 Fd. plastic RLS Cap, flush, in approx ctr. of E-W B.Top road; in line with newer fence to north.

12 Fd. 1/2" rod, with RLS Cap; Perla-Stout, L. Czubek, RLS. Ctr. of N-S gravel road is 5'± east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-7

Fd. 1 1/4" pipe raised w/1"X1' pipe		
Light Pole w/MDSH tag	S15°W	33.60
P.Pole	S85°W	78.29
16" Cherry	N63°E	90.04

G-6

Fd. re-rod & Set Ced.Post w/Loc. Tag.		
Ctr of U.S. 131	Due N.	45'±
8" R.Pine	S76°E	17.98
10" (Cluster of 4) Maples	S21°E	33.35
Conc. Rd. R/W Marker	S04°W	25.0

G-7

Fd. R.L.S. Cap in B.Top road		
38" Beech	Due N	34.03
34" Maple	N84°E	133.40
9" Cherry	S18°W	40.90

SIGNED BY Carl F. Roser 9-18-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BOARDMAN TOWNSHIP
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET