LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 26 N., R. 8W W.	I-1
2. PROPERTY CONTROLLING IN SECTION _____	,T. _____ N. S., R. _____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 11-23-77, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. (continued)
Monumented & Witnessed Govt. Re-survey corner. Verba, RLS for Mich. Con. Gas Co. was here & Wit. (side nails) three R.Pines which we re-faced, scribed, and booked new brg's. & dist. to face of trees.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-1 Recovered 1850 (Twp.Line) & 1852 (Twp. Sub'n)Govt. re-survey cor. Fd. old marked post and following remains of U.S.B.T.'s: 12" Y.Pine stump showing excellent lower face, N72°E, 4.0'; 30" Y.Pine stp. remains, N60°W, 18.5'; 18" W.Pine Stp. showing excellent lower face, S17°W, 19.8'; Y.Pine stp.-roots, S38°E, 34'. also recovered position of original Govt. Survey (1837+) standard corner from remains of both USBT's; 15" Y.Pine Stp., N3°W, 28.4' & 9" Y.Pine stub (15'+) showing excellent upper & lower face, N77°E, 11.2' (cut stp. off & took excellent USBT specimen to office). Original cor. position is 95'± E. & 10'± N. of Re-survey cor. (continued)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-1
Set D.N.R. Mon. & Ced.Post
at 1850 Govt. Resurvey cor.

13" R.Pine	N75°E	44.4'
15" R.Pine	S50°E	33.4'
16" R.Pine	S28°W	20.0'

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

SIGNED BY Carl F. Roser 9-18-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BOARDMAN TOWNSHIP
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET