

LANSING Forestry LAND CORNER RECORDATION CERTIFICATE
 FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

File # 298

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>6</u> T. <u>27</u> N. <u>5</u> R. <u>5</u> E. W.		<u>A-2, A-3</u>
2. PROPERTY CONTROLLING IN SECTION _____ T. _____ N. _____ S. R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ S. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

STATE OF MICHIGAN }
 COUNTY OF KALKASKA }
 FILED 13th DAY OF
 Feb. A. D. 1974 AT 9:00
 O'CLOCK A. M.
Marshall J. Metz
 REGISTER OF DEEDS
 REGISTER OF DEEDS STAMP AND
 FILING NUMBER

I, James L. Fletcher do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on January 27 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
 None

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

SEC. 6, W $\frac{1}{4}$ Cor. Fd. $1\frac{1}{2}$ " Pipe
SEC. 6, SW Sec. Cor. Fd. $1\frac{1}{2}$ " Pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

W $\frac{1}{4}$ Cor., SEC. 6
 Nail in 6" Pine N20°W 25.05'
 Nail in 8" Cherry S45°W 56.92'
 Nail in 18" Cherry South 65.78'
SW Sec. Cor., SEC. 6
 Nail in 8" Pine S86°W 11.25'
 Nail in 10" Twin Pine S05°E 10.56'
 Nail in 18" Pine N05°W 36.56'

Note: CORNER'S shown on this sheet were recovered & recorded by R.L.S. Jim Fletcher. Jim had the loan of our old M. Shaaf notes. Although I have not checked these Cor's. I would have to accept them, unless I made a survey & could prove otherwise.

SIGNED BY James L. Fletcher DATE January 28, 1974

SURVEYOR'S MICHIGAN REGISTRATION NO. 19830
 FOR STATE AND UNITED STATES AGENCIES _____

SIGNED BY _____ DATE 9-16-74
 CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
 MICHIGAN REGISTERED LAND SURVEYOR

Also see SEC. 6 and E $\frac{1}{4}$ Cor. of Sec. 6 as recorded by Jim Fletcher - File # 297

