

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 28 ^{N.} R. 6 ^{W.} 	C-11
2. PROPERTY CONTROLLING IN SECTION 31 _____	T. 28 ^{N.} R. 6 ^{W.} 	1; 5; 9; 10
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ ^{N.} ^{S.} R. _____ ^{E.} ^{W.} 	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 16, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument and accessories and/or subsequent restoration:~~

C. (continued)

	9	10
	Fd. 3/4" rerod w/plastic cap & steel ^{fn.} post & set cedar post w/loc. tag.	Set 5/8" x 36" rerod & cedar post w/loc. tag
	8" Maple S77°E 26.48	10" Maple N69°W 35.4
	12" Maple S63°W 24.10	8" Maple N06°W 27.3
	8" Maple N43°W 20.75	6" Maple S52°E 8.5
	10" Ironwood N27°E 9.35	5" Maple S02°W 30.3

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- C-11 A. V. Courtright found old cedar post and set rerod.
- 1 Established 1/16 corner S.P.
 - 5 Found 3/4" rerod by A. V. Courtright.
 - 9 Found 3/4" rerod by A. V. Courtright.
 - 10 Established 1/16 corner S.P.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11	1	5
Fd. 5/8"x18" rerod & set cedar post w/loc. tag.	Set 3/4"x48" rerod & cedar post w/loc. tag.	Fd. 3/4" rerod w/plastic cap & set cedar post w/loc. tag
12" Cedar N40°E 33.18	6" Cedar N37°W 22.1	8" Maple S11°W 28.00
14" Cedar S44°E 45.44	11" Maple S76°E 28.3	10" Maple S63°W 27.46
16" Cedar S46°W 32.73	6" Maple S07°E 15.3	7" Maple S49°E 15.7
	9" Hemlock S58°W 33.3	9" Maple N69°E 22.3
	Ctr. E-W swp. road Due N 3'±	


SIGNED BY Carl F. Roser DATE 10-31-77

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____

COLD SPRINGS TOWNSHIP
KALKASKA COUNTY