LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 28 N., R. 5 W.	D-9;
2. PROPERTY CONTROLLING IN SECTION 20	T. 28 N., R. 5 W.	7; 16;
3. MISCELLANEOUS PROPERTY IN SECTION 20	T. 28 N., R. 5 W.	1344.12 E OF D-9

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on JANUARY 12, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on JANUARY 12, 19 83, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. CONTINUED:

~~Description of original monument and accessories and/or subsequent restoration~~

1344.12 E OF D-9 - CONTINUED: 1919-1920.

C. CONTINUED:

16

FD 1" X 24" PIPE; ADDED CEDAR POST W/LOC TAG.

* 15" W. BIRCH	S20°E	17.6
*11" W. BIRCH	S43°W	35.3
7" MAPLE	N25°W	24.4
M.C. - 2" PIPE W/T COUPLING	S89°29'E	34.11

1344.12 E OF D-9

FD 2" PIPE W/T & CEDAR POST.

24" W. PINE STUMP	N47°W	8.9
24" W. PINE STUMP	S14°W	20.8
E 1/8 COR ON SO. LINE SEC 20	N89°29'W	34.11

* = 1968 DEPT. B.T.'S

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-9 - DEPT MON (KJO 1968) PER B.L. CAUKINS POST AND B.T.'S; CAUKINS FIELD NOTES AT ANTRIM COUNTY ROAD COMMISSION.

7 - FD 1" PIPE INSIDE 1 1/2" PIPE AS RECOVERED BY DEPT. SURVEY IN 1968 FOR NORTH M.C. ON E. LINE OF SEC. 20 AND PERPETUATION OF U.S. MC; ALSO NORTH 1/8 COR ON E. LINE OF SEC. 20 PER B.L.C. FITS B.L. CAUKINS SURVEY DATED MAY, 1920; PG 39 & 47 OF CAUKIN'S NOTES AT ANTRIM CO. RD. COMM.

16 - FD 1" X 24" PIPE FOR 1/8 COR AS ESTABLISHED BY DEPT. SURVEY IN 1968-1969.

1344.12 E OF D-9 - 2" PIPE WITH "T" ON TOP AS SET BY DEPT. IN 1968 TO PERPETUATE MEANDER COR ON WEST SIDE OF PAPOOSE LAKE PER B.L. CAUKINS SURVEY

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-9

FD DEPT MON; ADDED CEDAR POST W/LOC TAG.

*10" TWIN MAPLE	S60°W	11.5
* 5" MAPLE STUMP	S50°E	15.1
6" MAPLE	S10°E	38.0
6" MAPLE	N45°W	42.1
CTR E-W TRAIL	NORTH	12'

7

FD 1" PIPE INSIDE 1 1/2" X 42" PIPE; ADDED DNR ALUM CAP & SET CEDAR POST W/LOC TAG.

9" RED PINE	N30°E	29.76
5" W. PINE	N20°W	72.80
7" W. PINE	N64°W	26.77

* = 1968 DEPT. B.T.'S

SIGNED BY Carl F. Roser 5-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BLUE LAKE TWP.
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET