LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 28 N. S., R. 5 E. W.	D-8;
2. PROPERTY CONTROLLING IN SECTION 20	,T. 28 N. S., R. 5 E. W.	8
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on JANUARY 13, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. CONTINUED:

~~XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX~~

~~XX Description of original monument and accessories and/or subsequent restoration X~~

D-8 CONTINUED - FOR CTR OF SEC 20.

8 - DROVE 5/8" X 36" REROD FOR NW COR OF NE-SW OF SEC 20 MID-WAY & ON LINE BETWEEN FD CTR & W 1/4 COR OF SEC 20. THIS POSITION FITS 1920 B.L. CAUKINS B.T. EXACTLY.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-8 FD 3/8" X 18" REROD W/RLS CAP #19830 BESIDE 1' X 1' X 1' RED STONE. ROD WAS IN OLD ROTTED OFF POST BOTTOM. PULLED 3/8" REROD & DROVE 1/2" X 36" PIPE & PLACED 3/8" ROD BACK INSIDE 1/2" PIPE. A 3/4" X 5' PIPE (2 1/2' ABOVE GROUND) WAS S24°21'E, 1.04'; WE DROVE THIS PIPE FLUSH WITH GROUND. B.L. CAUKINS HAD SQ. POST AT CTR. OF SEC 20 IN JUNE 1920 BASED ON HIS SEC SUBDIVISION. DRAGOO SURVEY FOR "PLAT OF INDIAN LAKE" IN 1949 IS TIED TO CTR OF SEC 20. SHADKO SURVEY OF P.A.S. #40-11 TIED TO "PLAT OF INDIAN LAKE" & CTR OF SEC 20 (FD 4"X 4" SQ'D CEDAR STK) IN 1955. FLETCHER'S 3/8" REROD FITS ABOVE LISTED PRIOR SURVEY'S & WE ACCEPTED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-8

FD 3/8"X 18" ROD W/RLS CAP #19830 & SET CEDAR POST W/LOC TAG.

*13" HEMLOCK	N52°W	24.45
*13" MAPLE	N85°E	28.77
* 6" IRONWOOD	S35°W	14.00
3/4" PIPE (FLUSH)	S24°21'E	1.04

* = RLS, J. FLETCHER B.T.'S

8

DROVE 5/8"X 36" REROD W/RLS CAP & SET CEDAR POST W/LOC TAG.

10" MAPLE	N55°E	7.8
3" MAPLE	S30°W	9.7
*13" BEECH	N04°W	14.8

* = B.L. CAUKINS 1920 B.T.

SIGNED BY Carl F. Roser 05-02-83 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BLUE LAKE TWP.
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET