

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>28</u> N. <u>5</u> R. <u>5</u> W.	M-2, <u>I-1</u> , <u>G-1</u>
2. PROPERTY CONTROLLING IN SECTION <u>2</u>	T. <u>28</u> N. <u>5</u> R. <u>5</u> W.	<u>15</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ R. _____ E. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October 3, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

G-1

~~A. Description of original monument and accessories and/or subsequent restoration:~~

C. (continued) Fd. DNR Mon. from Previous Dept. Survey & Set cedar post  
 7" Maple S86°E 78.08'  
 8" Cherry S05°W 74.38'  
 6" Cherry S48°W 31.10'  
 7" Twin Maple N39°W 76.85'  
 Cor. to Sec's 33 & 34, T29N-R5W (Fd. Dept. Mon.) is S89°31'E, 9.90'  
 Cor. on random line E & S.

M-2 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  
 Set D.N.R. Mon. on line & at proportionate Mea. to U.S. between fd. Sec. Cor's. to N & S. M. Schaaf Mon. (in error) is N74°09'W, 28.5',

I-1 Fd. Dept. Mon. from 1957 Dept. Survey (KJO), Cor. Comm. to Sec's 34 & 35, T29N-R5W, is S89°30'E, 6.60', being a fd. Bronze Cap. on 1" pipe & set ced. post W/Loc. Tag.

15 Establish 1/8 cor. equidistant & on line between Sec. cor, West & 1/4 Cor. East.

G-1 Recovered Dept. Mon. from previous Dept. Survey (1957) as established by proportionate measurement to U.S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-2 Set DNR Mon. & cedar post 4" Spruce S83°W 40.8' 9" Balsam N48°E 13.3' 3" Maple S39°E 158.0' W.Pine stp. S45°E 32'±	I-1 Fd. Dept. Mon. from previous Survey (Bronze Cap on 1" pipe) & Set ced. post W/Loc. Tag 4" Twn. Maple S76°W 32.1' 13" Twn. Ir. Wo. S52°E 16.9' 4" Map N40°E 22.9' 12" Ironweed in Cluster N45°W 15.0' Cor. on Rand. Line E-W-S.	15 Set 5/8"x36" Re-rod W/plastic cap & cedar post W/Loc. Tag 9" Maple N53°E 24.2' 4" Maple in Clump S24°E 6.8' 11" Maple N30°W 43.9'
---	--	--

SIGNED BY Carl F. Roser 2-5-78 DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

BLUE LAKE TOWNSHIP  
KALKASKA COUNTY