## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

April 4 1922, found, recovered, restored, established or re-established as expressed below and in con-	FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER		
3. MSCHLANDOUS PROPERTY IN SECTION	1. PUBLIC LAND SURVEY 18	T	7-6	3	
A LOT NO	2. PROPERTY CONTROLL- ING IN SECTION—	1 ,T. 5 N. R. 9	2-c	Lesi'	
S. PRIVATE CLAIMS  1. D. Scott  do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioped in lines 1 and 2 above (identified with circles on index code diagram—over) vere, in a field survey on 1921.  1. D. Scott  do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioped in lines 3 and 2 above vere, in a field survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a coget of law. Furthermore, that the corner points mentioned in lines 3,4 and 3 above were, in a field survey in Applit 4 1922, found, recovered, restored, established or re-established are established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:  A. Description of original monument and accessories and/or subsequent restoration:  B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  Found 1' Iron Pipe 17 Monument E. at Road Intersection  of 8476 g Marse Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1' Iron Pipe 10 Monument Boy  M. 28° 5. 25.0' Telephone Pole  N. 48° E. 39.0' Street Sian Rash  S. 28' W. 100.0' Telephone Fole  N. 40° W. 47.75 Stop Sian Fash  S. 28' W. 100.0' Telephone Fole  N. 20' W. 47.75 Stop Sian Fash  S. 28' W. 100.0' Telephone Fole  SERVEYOR'S MICHIGAN REGISTRATION NO. 15099 (SEA.)  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE  DATE  DATE  DATE	3. MISCELLANEOUS PROPERTY IN SECTION——	,T <sup>N.</sup> , R <del>E</del> .		\ 	
D. Scott   do bereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioped in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on PARI   4	4. LOT NO , REC	ORDED PLAT			
the corner points mentioned in lines I and 2 above (identified with circles on index code diagram—over) were, in a field survey on April 4 1922, established, re-established, monumented, re-nonumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a cognt of law. Furthermore, that the corner points mentioned in lines 3,4 and 3 above were, in a field survey on HPRII 4 1922, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:  A. Description of original monument and accessories and/or subsequent restoration:  B. Description of original monument and accessories and/or subsequent restoration:  FAUND 1 TROIT Pipe 111 Manument E. 27 Road Intersection  of 847h \$ Messe Lake Rais.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1 Tran Pipe 111 Manument Bost  A. 28° E. 75.0' Telephone Pole  N. 48° E. 39.6', Street Sian Rash  N. 20° H. 47.75 Stop Sian Rash  S. 28° E. 71.0' M.M. Corner of School House Blds.  S. 28° E. 71.0' M.M. Corner of School House Blds.  S. 28° W. 100.0' Telephone Pole  SIGNED BY DATE  OATE  OATE  OATE  DATE  DATE  DATE	5. PRIVATE CLAIMS			1	
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  FAUND 1" IRON Pipe IN Monument & 27 Road Intersection of 8474 & Monse Lake Rais.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Boy  N. 28° E. 75.0" Telephone Pole N. 48° E. 39.6", Street Sign Post N. 20° N. 47.75 Stop Sign Post S. 28° E. 71.0" N.W. Corner of School House Bldg. S. 28° W. 160.0" Telephone Pole SURVEYOR'S MICHIGAN REGISTRATION NO. 15039  CHIEF OF EURICY PARTY  APPROVED AND SIGNED BY  UNDER MICHIGAN REGISTRATION NO. 15039  CHIEF OF EURICY PARTY  DATE  DATE  DATE	the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on April 4 1922, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 1922, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of				
Found 1' Iron Pipe in Monument B. at Road Intersection of 847h & Morese Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  3" Iron Pipe in Manument Box  5" Iron Pipe in Manument Box  6" Iron Pipe in	A. Description of original mo	nument and accessories and,	or subsequent restoration:		
Found 1' Iron Pipe in Monument B. at Road Intersection of 847h & Morese Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  3" Iron Pipe in Manument Box  5" Iron Pipe in Manument Box  6" Iron Pipe in					
Found 1' Iron Pipe in Monument B. at Road Intersection of 847h & Morese Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  3" Iron Pipe in Manument Box  5" Iron Pipe in Manument Box  6" Iron Pipe in					
Found 1' Iron Pipe in Monument B. at Road Intersection of 847h & Morese Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  3" Iron Pipe in Manument Box  5" Iron Pipe in Manument Box  6" Iron Pipe in					
Found 1' Iron Pipe in Monument B. at Road Intersection of 847h & Morese Lake Ras.  C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  1" Iron Pipe in Manument Box  2" Iron Pipe in Manument Box  3" Iron Pipe in Manument Box  5" Iron Pipe in Manument Box  6" Iron Pipe in	B. Description of corner evid	ence found and/or method ar	oplied in restoring or re-estab	lishing corner:	
1" Iron Pipe in Monument Box  1" Iro	Found l'Iron Pipe in Monument Bax at Road Intersection				
1" Iron Pipe in Monument Box  1" Iro	C. Description of monument	for corner and accessories	established to perpetuate loc	ating the position of the corner:	
N. 48° E. 39.6' Street Sign Post  N. 20° W. 47.75' Stop Sign Post  S. 28° E. 71.0' N.W. Corner of School House Bldg.  S. 28° W. 100.0' Telephone Pole  SIGNED BY DATE 4-4-72  SURVEYOR'S MICHIGAN REGISTRATION NO. 15039 (SEAL)  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE  CHIEF OF BURVEY PARTY  APPROVED AND SIGNED BY MICHIGAN REGISTRATION DATE	•		• ,		
N. 48° E. 39.6' Street Sign Post  N. 20° W. 47.75' Stop Sign Post  S. 28° E. 71.0' N.W. Corner of School House Bldg.  S. 28° W. 100.0' Telephone Pole  SIGNED BY DATE 4-4-72  SURVEYOR'S MICHIGAN REGISTRATION NO. 15039 (SEAL)  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE  CHIEF OF BURVEY PARTY  APPROVED AND SIGNED BY MICHIGAN REGISTRATION DATE	N. 28° E. 75.0'	Telephone Pole			
SIGNED BY	N. 48° E. 39.6'	Street Sien Post			
SIGNED BY	N. 20° W. 47.75	Stop Sian Post			
SIGNED BY	S. 28° E. 71.0'	N.W. CORNER OF S	School House Bldg.		
SURVEYOR'S MICHIGAN REGISTRATION NO. 13 039 (SEAL)  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY	5.28° W. 100.0'	Telephone Pale			
SURVEYOR'S MICHIGAN REGISTRATION NO. 15039 (SEAL)  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY			DATE <u></u> 4-	4-72	
SIGNED BY DATE	· -	GISTRATION NO. 1503	9	(SEAL)	
APPROVED AND SIGNED BY DATE DATE	FOR STATE AND UNITED S	TATES AGENCIES:			
APPROVED AND SIGNED BY DATE DATE	SIGNED BY	CHIEF OF SURVEY PARTY	DATE		
(SEAL)	APPROVED AND SIGNED BY	MICHIGAN DEGICTEDES :	AND SURVEYOR DATE		
		miterial and a second of the s		(SEAL)	
	SURVEYOR'S MICHIGAN REC	GISTRATION NO			

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

27.7