

## SURVEY &

JAN 2 3 1996

CO	M	M	IS	S	ION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For	corners in		KENT COUNTY RE	MONUMENTATION	\ 35 R S		
	Kent (County)	Locate	d in: Corner	r Code #	DEC 2		
1.	Public Land Surve	T T	R 11W		OF MICHIGAN TY OF KEHT OF OR RECOR		
	Property Controlli in Section	ng ST ST	RR		`8900 <sup>2 8 2</sup>		
	Miscellaneous Property in Sec.	S T	R		egister of Deeds Stamp & File Number		
4. 5.	Lot No Private Claims	, Recorded Plat		<u>.</u>	ABCDEFGHIJKL		
do h ment in the Land 4 and Decr	ereby certify that tioned in lines 1 and e current manual of I Management or by d 5 above were in	under requirements of F d 2 above were in conform f survey instructions of the a decree of a Court of La conformance with the rule _aw; established, re-esta	P.A. 74 Michigan P.A. of sance with regulations and reconstructions and reconstructions and reconstructions and/or that the corner possion of the Michigan Board of ablished, monumented, respectively.	1970, the corner points rules therefore as required tof the interior, Bureau of pints mentioned in lines 3, of Land Surveyors or by a	3 4 8 9 10 11 12- 5 6 18 17 16 15 14 13- 7 8 19 20 21 22 23 24- 9		
NOT	E: Not more th on this certi		same town and range, m	nay be recorded	10 30 29 28 27 26 25- 11 12 31 92 33 34 35 36-		
A.	Description of d	original monument and	accessories and/or subs	equent restoration:	13		
B-4	This corner was not originally set by the G.L.O.						
	1966-1987 1974	Survey Notes L.C.R.C. #756	Williams & Works Williams & Works	Found Plat Monu Conc. Plat Monur			
				PEE	345 1990 KENT COUNTY R APPROVED 10/26/95 NIRMAN Trany Muhee		
B.	Description of c	orner evidence found a	and/or method applied in	restoring or reestablishi	ng corner:		
B-4	3.5' South and	exxel iron #12579 in sam 2.5' East of true Cente ing back to 1966.	ne position as concrete plant of Section and has be	at monument which check een accepted for center	s per L.C.R.C. #756. This iron is by Williams & Works and Exxel		
	L.C.R.	C. #756	•				
	CP-MBT pole S0 Light N45°E 56.3		1 				
				·			
					·		
Э.	Description of m	nonument for corner and	d accessories establishe	d to perpetuate locating	the position of the corner:		

Replaced Exxel iron with a Standard 4" x 30" Kent County Monument.

Nail in W face P. pole S 05° E 11.45' Nail in N face L. pole N 45° E 56.30' Nail & K.C. remon, tag in N face P. pole S 80° E 146.45' C/L top of hyd. N 45° E 14.90'

25854

Signed by

CENSED LAND SUF

RANDY J.

KOLEHOUSE

LAND SURVEYOR