

MAR 03 1998

KENT COUNTY REMONUMENTATION

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

REG. OF DEEDS

Lucy Spauld

97 APR 29 AM 8:20

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

For corners in
KENT COUNTY
(County)

Located In: Corner Code #

- 1. Public Land Survey T 6N R 9W B-13
- T R
- T R
- T R
- 2. Property Controlling S T R
- in Section S T R
- 3. Miscellaneous S T R
- Property in Sec. S T R

9797

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

I, Kirk Breiteis, in a field survey on Jan. 23, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

B-13	1830	GLO	Mullett	Set Post
		Kent Co. Wit.		3/4" Iron
	1979	LCRC #3266	Hay	3/4" Iron
	1996	LCRC #9597	Jonker	Set Kent County Monument

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Robert J. Jonker on 7/24/96 and was recorded per LCRC #9597

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-13 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Robert J. Jonker in place of the 4" Spike over a Rerod he found. Both Rerod and Spike checks with Kent Co. Wit. and LCRC #3266.

LCRC #9597

Remon. tag E. side 18" Oak	S00°W	37.62'
Remon. tag W. side 18" Hickory	N14°E	32.03'
Remon. tag NW side 28" Oak	S62°W	71.05'
PK Nail E. side P. Pole	N04°E	53.02'
N 1/4 Sec. 6, Bowne Twp.	East	85.15'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-13 Standard Kent County Monument

Nail & KC Remon. tag E. side 20" Oak	S00°W	37.56'
Nail & KC Remon. tag W. side 20" Hickory	N14°E	32.03'
Nail & KC Remon. tag NW side 34" Oak	S62°W	71.05'
PK Nail E. side Power Pole	N04°E	53.02'
N 1/4 Sec. 6, Bowne Twp. (Kent Co. Mon.)	East	85.18'



Signed by *Kirk Breiteis*
Surveyor's Michigan License No. 30077

Date 3/27/97

P.A. 345 1990 KENT COUNTY
PEER APPROVED 3/27/97
CHAIRMAN *Harry Hubell*