

SURVEY & REMONUMENTATION



Kent County Remonumentation

STATE OF MICHIGAN COUNTY OF KENT RECEIVED FOR RECORD

APR 2 8 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

94 NOV 29 AH 9: 19

For corners in Kent		· ·····g····q·····		1.20	
		Located In:	Corner Code ##	and the second	
	(County)			REG. OF DEEDS	
1.	Public Land Survey	T <u>6N</u> R <u>12W</u> T R	E-10		
		T R			
		T R			
2.	Property Controlling in Section	S T R S T R		7432	
3.	Miscellaneous	S T R		Register of Deeds Stamp & File Number	
	Property in Sec.	S T R		riogister of Seeds Statisfied The Hungber	
4.	Lot No,	Recorded Plat	:		
5.	Private Claims				

March 29 Randy Kolehouse , in a field survey on do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

P.A. 345 1990 KENT COUNTY E-10 1831 G.L.O. Notes L. Lyon Set Post PEER APPROVED 1 1963 Wit. Map K.C. Surveyor Iron 1972 L.C.R.C. #364 Exxel Engineering 1/2" Iron in Mon. Box 1974 Survey Records Williams & Works 1" Iron in Mon. Box L.C.R.C. #2347 Fnd. 1/2" Iron in Mon. Box/Set K.C. Monument 1981 Exxel Engineering

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering, Inc., on December 11, 1981 and was recorded per L.C.R.C. #2347.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-10 Found K.C. Monument 2' + W of C/L of Ivanrest Avenue running N-S per L.C.R.C. #2347 as set by Exxel Engineering in place of a 1/2" iron in monument box which checks 1963 K.C. surveyor records of L.C.R.C. #364.

L.C.R.C. #364

L.C.R.C. #2347

NE cor. porch fndn. NW 69.87'

NE cor. hse. fndn. N 55° W 69.87' SE cor. hse. fndn. N 76° W 55.40' Nall & K.C. remon, tag in E side 28" Maple S 28° W 91,61' SW cor. metal building N 84° E 153.03'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-10 Standard Kent County Monument

NE cor. hse. fndn. N 55° W 69.87' SE cor. hse. fndn, N 76° W 55.40' Nail & K.C. remon, tag in E side 28" Maple S 28° W 91,61' SW cor, metal building N 84° E 153.03'

RANDY J. KOLEHOUSE AND

25854 Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED JAN., 1983