

FEB 14 1997

COMMISSION KENT COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KENT COUNTY

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8N R 11W M-9
T 8N R 10W A 9

2. Property Controlling in Section

S T R
S T R
S T R
S T R

3. Miscellaneous Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

REG. OF DEEDS
95 MAR 20 AM 9:00
STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
9126
Register of Deeds Stamp & File Number

I, Kirk Breitels, in a field survey on Jan. 23, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

P.A. 345 1990 KENT COUNTY
PEER APPROVED 3/2/96
CHAIRMAN Harry [Signature]

Grid table with columns A-M and rows 1-13. Contains numbers 6-36.

A. Description of original monument and accessories and/or subsequent restoration:

Table with columns: M-9, Year, Description, Location, Monument Type. Includes entries for 1837, 1972, 1979, 1981, 1988.

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Robert J. Jonker on 8/20/81 and was recorded per LCRC #1980.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-9 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Robert J. Jonker in place of the Iron he found inside a Mon. Box. Said Iron checks with Kent Co. Wit. and LCRC #1310. LCRC #1980 & #4889

Table with columns: Description, Bearing, Distance. Includes entries like 'PK Nail & KC Remon. tag in curb joint S43°E 48.28''.

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

Table with columns: Description, Bearing, Distance. Includes entries like 'PK Nail & KC Remon. tag in curb joint S43°E 48.28''.



Signed by [Signature]

Date 2/6/96

Surveyor's Michigan License No. 30077