



MAR 08 1999

LAND CORNER RECORDATION CERTIFICATE

For corners in SEC		SECTION	Filin	-	ment of Act 74, Mich. P. UNTY REMONUMENTATION				
	Kent (County)	·	Located in:	Oakfield Township	Corner Code #	OF DEE			
1.	Public Land Survey	У	T	R <u>9W</u> R R R	B-13	DS (2		
2.	Property Controllin in Section	g s s	_ T i	R R		1095	3		
3.	Miscellaneous Property in Sec	s	T 1	R		Register of Deed			

1.	Public Land Survey		T		E				SO	3	8: 00	ECORD			
			Т												
2.	Property Controlling	s	т												
	in Section							1	09	53					
3.	Miscellaneous										_				
	Property in Sec.						'	Registe	of De	eds St	amp 8	· File I	Numbe	:r	
4.	Lot No,	Becorde	d Plat												
5.	Private Claims	. 1000146	a , iai					<u>.</u>							
			· · · · · · · · · · · · · · · · · · ·					- A	в с	D E	F (3 H	l j	K L	. М
					•			2	_	_ [_]	_	_ i_			
								3	Ĭİ	Ĭ	Ī	ΙĬ		1 (
I, _	Randy Kolehouse	, in a	field survey	onJa	inuary 30	19	98	آ رُ						\top	
do	hereby certify that under	er requiren	nents of P./	A. 74 Michig	gan P.A. of	1970, the co	rner points	*	-7-H	-8-	9 	—10— [12	·
mei	ntioned in lines 1 and 2 at	oove were	in conformar	ice with regu	ilations and r	ules therefore	as required	5						-	_
in ti	he current manual of surv	ey instruct	tions of the U	Jnited States	Department	of the interior	, Bureau of	6	18		18		14-	17	3—
Lan	nd Management or by a de	ecree of a	Court of Law	and/or that	the comer po	oints mentione	d in lines 3,	7 -					+	+	_
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, 8 19 20 21 22 23 24							4								
	nd as expressed below:	Cotabilori	ou, ie-estab	nancu, mom	umomeu, re	monumented,	recovered,	9					$\bot \bot$	$\perp \perp \downarrow$	
ŀ	TE: Not more than 4	corners	all in the sa	me town a	nd range m	av he record	lod	10	_30		 			1 2	
•	on this certificat		III III JE	anio tomila	na range, n	ay be record	ieu	[ï	Ĩ		-,,			<u> </u>

Description of original monument and accessories and/or subsequent restoration:

					13
B-13	1837	G.L.O. Notes	N. Brookfield	Set Post	P.A. 345 1990 KENT COUNTY
	N/A	Witness Map	K.C. Surveyor ,	N/A	PEER APPROVED 9/24/9
	1978	L.C.R.C. #1122	Williams & Works	3/4" fron (B-1, T8N, R9W)	07 711
	1978	L.C.R.C. #1205	Nederveld & Jonker	3/4" Round Iron	CHAIRMAN Jamy
	1980	L.C.R.C. #1731	Williams & Works	Fnd. 3/4" Iron Pipe / Set K.0	C. Monument
	1989	L.C.R.C. #5175	John Bueche	K.C. Monument	
	1997	L.C.R.C. #9636	Kirk Breitels	K.C. Monument	

Note: This corner is common with B-1, T8N, R9W.

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Williams & Works on 12/23/80 and was recorded per L.C.R.C. #1731.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found a Standard Kent County Monument 6' South of the C/L of 10 Mile Road (bit.) running East and West and 5' East of the C/L of Greenland Drive (gravel) running North per L.C.R.C.'s #1731, #5175, and #9636 as set by Williams & Works in place of a 3/4" iron pipe they found which checked L.C.R.C.'s #1205 and #1122.

L.C.R.C. #1731

K.C. Remon. Tag & Nail in N. Side P. Pole S 65°E 81.41' K.C. Remon. Tag & Nail in NW Side P. Pole S 75°W 92.29' NW Cor. Hse. Fnd. S 50°E 106.14' NE Cor. Hse. Fnd. S 05°W 102.26'

L.C.R.C. #9636

Nail & KC Remon, tag N side P. Pole S 65° E 81.41' (m. 81.46') Nail & KC Remon. tag NW side P. Pole S 75° W 92.29' (m. 92.30') NW corner house foundation S 50° E 106.14' (m. 106.20') NE corner house foundation \$ 05° W 102.12'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-13 Standard Kent County Monument

Surveyor's Michigan License No.

Nail & K.C. remon. tag on N side P. pole S 65° E 81.46' Nail & K.C. remon. tag on NW side P. pole S 75° W 92.30'

Nail & K.C. remon. tag on SW side guard post N 40° W 47.64'

Nail & K.C.remon. tag on E side 8" Oak N 05° W 95.66"

NW cor. fndn. S 50° E 106.20'

NE cor. hse. fndn. S 05° W 102.12' C/L of bit. road running E-W, North 6.0' C/L of gravel road running N, West 5.0'

NW cor. brick garage S 30° W 109.33' Signed by,

25854

RANDY J KOLEHOUSE No

2585 ARDO LAND

FORM APPROVED BY MICHIGAN STA