

1993

other

MAY 09 1996

COMMISSION

Kent County Remonumentation  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in

Kent

(County)

Located In:

Corner Code #

1. Public Land Survey

T \_\_\_ R \_\_\_  
T \_\_\_ R \_\_\_  
T \_\_\_ R \_\_\_  
T \_\_\_ R \_\_\_

Other Code

#9

2. Property Controlling in Section

S 27 T 10N R 9W  
S \_\_\_ T \_\_\_ R \_\_\_

Spencer Twp.

3. Miscellaneous Property in Sec.

S \_\_\_ T \_\_\_ R \_\_\_  
S \_\_\_ T \_\_\_ R \_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

John C. Bueche

April

19 93

I, \_\_\_\_\_, in a field survey on \_\_\_\_\_, 19 \_\_\_\_\_, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This point never set by G.L.O.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set witness monument 149.75' S of N 1/4 Cor Sec 27 on N - S 1/4 line Sec 27.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Std. K.C. Mon. (Harrison 4" x 30") 149.75' S of the N 1/4 cor. Sec. 27 on the N-S 1/4 Line of Sec. 27  
Nail & K.C. Remon. Tag in N side Service Pole N 85° E 23.37'  
Nail & K.C. Remon. Tag in W side PP S 40° W 86.29'  
Nail & K.C. Remon. Tag in W side 14" Maple N 35° E 27.94'  
NE cor. hse. #12395 brick N 15° W 83.92'  
PK in bit. (18 Mile Road) South 26.25'  
S edge Lake North 100'±

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

6797

Register of Deeds Stamp & File Number



Signed by

John C Bueche

Date

June 10, 1993

Surveyor's Michigan License No.

13027