LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 19	T. 10 N. R. 11 W.	B-7, B-8
2. PROPERTY CONTROLLING IN SECTION ____	,T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B-7 Leaded Stone.
Fence Post, North, 19.7'
M.B.T., NE, 98.37'
15" Oak, SW, 183.3'
18" Oak, South, 62.5'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-7 Found 1/2" Pipe.

B-8 Found 1/2" Rod at intersection fences north-south and west, measured distances matched distances reasonably from data on corner witnes map from Williams and Works.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-7 N 1/4 Corner, Section 19
Found 1/2" Pipe.
S 58° E, 122.31', Power Pole, Spike & Tag
S 05° E, 75.8', NW leg Transmission Tower
N 71° W, 92.08', Gas Line Marker Post #1021
S 65° W, 107.13', Power Pole, Spike & Tag
South, 1.5', ℄ Road

B-8 C 1/4 Corner, Section 19
1/2" Iron Rod.
West, 116.60', 30" W. Pine, Spike & T
S 09° E, 105.0', NE Leg of Transmissi Tower
S 52° W, 2.5', Fence Corner Post
N 45° E, 161.08', 22" W. Oak, Spike & Ta

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L Bissell (CHIEF OF SURVEY PARTY / MICHIGAN REGISTERED LAND SURVEYOR) DATE 11-20-80 (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655 Kent Co.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET