LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970.

FOR CORNERS OF–:   **LOCATED IN–:** | **CORNER CODE NUMBER**

1. PUBLIC LAND SURVEY __19__ T. __10__ **N.** R. __11__ **W.** | A-9

2. PROPERTY CONTROLL-ING IN SECTION _____ ,T. _____ **N. S.,** R. _____ **E. W.** | C 1/8 Cor. of SW ~~Frl. 1/4~~

3. MISCELLANEOUS PROPERTY IN SECTION _____ ,T. _____ **N. S.,** R. _____ **E. W.** |

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____ | **REGISTER OF DEEDS STAMP AND FILING NUMBER**

I, __Donald L. Bissell__ , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on __September__ , 19 __80__ , established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ , 19_____ , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

```
A-9   1" Iron
      6" Oak, NE, 40.3
      8" W. Cherry, NW, 45.95'
      8" Oak, SE, 46.30'
      1" Iron, E, 33.0'
      1944
```

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

```
A-9   Found 1" Iron                           C 1/8 Cor. of SW Frl. 1/4, Section 19
      S 19° E, 47.21', 15" R. Oak            Found 1" Iron rod. Replaced with concrete
      N 36° W, 45.34', 12" & 15" Twin        monument 0.9' South of iron location, to
                         W. Cherry           put it at the intersection of the 1/8
      N 62° E, 40.33', 13" & 15" Twin        lines.
                         W. Oak
```

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

```
A-9   SW Corner, Section 19                   C 1/8 Cor. of SW Frl. 1/4, Section 19
         1" Iron                              Set 4" x 36" concrete monument
      S 48° W, 62.80', 12" W. Oak, Spike & Tag   S 09° E, 33.64', 14" R. Pine, Spike & Tag
      S 19° E, 47.21', 15" R. Oak               S 64° W, 73.39', 10" R. Pine, Spike & Tag
      N 36° W, 45.34', 12" & 15" Twin W. Cherry,  N 44° W, 96.33', 12" R. Pine, Spike & Tag
                         Spike & Tag           N 32° E, 48.45', Power Pole, Spike & Tag
      N 62° E, 40.33', 13" & 15" Twin W. Oak,
                         Spike & Tag
```

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____   (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _Donald L. Bissell_ DATE _11-20-80_
MICHIGAN REGISTERED LAND SURVEYOR   (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. __18655__   *KenT Co.*

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET