

MAR 19 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in KEWEENAW - REMON
(County) Located in:

Corner Code #

- 1. Public Land Survey T 57N R 32W
- T _____ R _____
- T _____ R _____
- T _____ R _____
- 2. Property Controlling S _____ T _____ R _____
- in Section S _____ T _____ R _____
- 3. Miscellaneous S _____ T _____ R _____
- Property in Section S _____ T _____ R _____

F-11

REGISTER'S OFFICE }
County of Keweenaw } SS
Received for Record, the 8th
day of November, A.D. 1996
at 11:00 o'clock A.M., and Recorded
in Liber _____ of LCR
on page 145
Robert Rosenbauer, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, R. W. CRAMPTON, in a field survey on JUNE 13, 1985, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
F-11 S 1/4 CORNER SECTION 28-SET POST- SUGAR 12 S50E 43, SUGAR 14 N60W 16

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
F-11 S 1/4 CORNER - 1" IRON PIN IN CONCRETE (FND)



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
F-11 THE 1" IP WITH 4" BRASS CAP WAS WITNESSED WITH SURVEY TAG NAILED TO:
CUT OFF UTILITY POLE N47W 5.30', 3" MAPLE TREE N33W 80.08',
10" ASPEN TREE S74E 67.35', 8" ASPEN TREE S7E 90.04'.

Justified by Peer Group
In accordance with P.A. 345
Co. Rep. [Signature]
Date 10/15/96

Signed by Robert W. Crampton
Surveyor's Michigan License No. 24591

Date OCTOBER 1, 1996