

Lake Co.

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. <u>18</u> N. <u>11</u> <u>W.</u> <u>W.</u>	H-9; I-9; I-10
2. PROPERTY CONTROLLING IN SECTION_____	, T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION_____	, T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970 the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 6-26-1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- H-9 Recovered 7/8"x30" Iron rod by corner fence post (Fn. N&E) which fit G. Johnson Witness.
- I-9 Recovered 1-5/8"x18" cast iron by rotted off corner fence post (old fence N&W) which fit two G. Johnson Wit.
- I-10 Accepted old Cedar corner post (fence gone) for 1/4 corner. Fits close to comp. position by single proportion.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-9			I-9			I-10		
Found iron, added std DNR Mon.			Fd. iron, added DNR Mon			Fd. Ced. cor. Fn. Post		
17" W. Oak	N50W	25.7'	& Ced. Gd. Post.			Set DNR Mon & Ced gd. post.		
23" R. Oak	S70E	10.9'	12" Maple	N21W	25.9	12" Tw Maple	N10W	12.5
			16" Maple	N36E	42.3	8" Beech	S23E	22.4'
			5" Tw Beech	S42W	22.7			


SIGNED BY Carl F. Roser DATE 9-24-73

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____