

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|--|---|----------------------|
| 1. PUBLIC LAND SURVEY _____ | T. <u>18</u> ^{N.} S. , R. <u>11</u> ^{E.} W. | <u>E-4; G-3; G-7</u> |
| 2. PROPERTY CONTROLLING IN SECTION _____ | T. _____, S. _____, R. _____, E. _____, W. _____ | _____ |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____ | T. _____, S. _____, R. _____, E. _____, W. _____ | _____ |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 6-28 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-4** Reestablished corner per standard B.L.M. instructions.
- G-3** Restored corner from two F. Jones Witnesses and one G. Johnson witness. Old corner of record.
- G-7** Restored corner form two possible U.S. witness remains (Pine Stumps) which fits corner positbn by double proportion within ±5'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

| E-4 | G-3 | G-7 |
|----------------------------|-----------------------------------|----------------------------|
| Set DNR Mon & Ced gd. post | Set DNR Mon. (buried) | Set DNR Mon & Ced Gd. Post |
| 7" w. Oak N23W 19.6 | 17" W. Oak N50E 93.7' | 15" W. Oak N25W 25.3 |
| 6" R. Oak N28E 16.5' | 16" W. Oak S13E 87.0 | 8" Cherry S40E 20.0 |
| 14" Oak S22W 25.7' | 9" Maple S60W 87.7' | 16" B. Oak S70W 24.6' |
| | E-W Fn. Due N 33' | |
| | Ctr. E-W gravel Rd Due N 2'± | |
| | Set Ced. Post w/loc tag Due N 33' | |


SIGNED BY Carl F. Roser DATE 9-24-73

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____