LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 18 N. ●., R. 12 ●. W.	A-12;B-12;B-13
2. PROPERTY CONTROLLING IN SECTION 31	,T. 18 N. ●., R. 12 ●. W.	10
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Jan. 16, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~Description of original monument and accessories and/or and/or recovered restoration~~

C. continued

10

Set R&R spk. in Ctr. of N-S Bit. Rd.
Ctr. Power line Due N 58'
20" Twin Maple S75°W 62.80'
Set cedar post w/Loc. Tag
Due E 33'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-12 Fd. 1/2" pipe, buried in approx. ctr. of N-S B. Top road. Corner fits 1954 Wits. by RLS, G. Blass.

B-13 Recovered 1" Iron in Mon. Box. that fit RLS, G. Blass Witnesses for S 1/4 Cor., Sec. 31, dated 1954.

B-12 Established ctr. of Sec. 31 at intersection of 1/4 lines.

10 Established 1/8 Corner per Std. B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12

Fd. 1/2" pipe, buried, raised with 1/2" pipe.

16" B. Oak	N45°E	57.0'
18" B. Oak	S42°E	62.0'
6" B. Oak	S86°W	48.34'

Set Cedar Post w/Loc. tag
Due E 33'

B-13

Fd. 1"X1" iron in Mon. Box. 1' S of U.S.-10 Ctr. line.

11" W.Oak	N35°E	86.2
14" B.Oak	S38°E	58.4
Power Pole	S03°W	41.45
Power Pole	N60°W	101.39

B-12

Set 5/8"X40" iron rod w/RLS cap. & Ced.Post w/Loc.Tag

6" R.Pine	N05°E	29.2'
4" R.Pine	S10°E	5.9'
4" R.Pine	N60°W	26.8'

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR
(SEAL)

SIGNED BY Carl F. Roser 1-18-79 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CHERRY VALLEY TOWNSHIP
LAKE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET