LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 18 N. S., R. 12 E. W.	E-11
2. PROPERTY CONTROLLING IN SECTION 28	,T. 18 N. S., R. 12 E. W.	8; 9; 14; 15
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 2, 19 77, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued)

14

Set 1 1/4"X24" round iron
4" B. Oak N85°E 40.1
5" B.Oak S35°E 43.6
Set Ced.w/loc.tag
Due E 33'

15

Fd. 3/4" iron 2' S of ctr. E-W rd.
12" B.Oak N15°W 42.26
9" W.Oak S02°W 32.87
Set Ced.Post w/loc.tag
Due N 33'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-11 Fd. 1/2" pipe that fits Blass Wit., buried, 3'± So. of ctr. of E-W sand road, 1.5'± W. of ctr. gravel road N. & ctr. Bit. rd. So.
8 Estab. 1/8 Cor. per Std. B.L.M. instructions.
9 Estab. 1/8 Cor. per Std. B.L.M. instructions.
14 Estab. 1/8 Cor. per Std. B.L.M. instructions.
15 Fd. 3/4" In. fits equidistant & on line between Sec. Cor. W. and 1/4 Cor. E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-11

Fd. 1/2" pipe
9" B.Oak N58°W 68.32
12" R.Pine N55°E 59.22
P.Pole S60°E 45.92
Set Ced.Post w/loc.tag
(beside Conc.Mon)
S45°W 47'

8

Set 5/8"X40" rod w/RLS
cap in ctr E-W rd.
4" B.Oak N43°E 29.92
5" B.Oak S15°E 49.07
Fd. 3/4" pipe
Due S 33.0

9

Set 1 1/4"X 20" round iron
4" R.Pine S58°E 61.1
8" B.Oak S35°W 35.20
Set Ced.Post w/loc.tag
Due S 33'
Fd. 1" pipe Due N 20.0

SIGNED BY Carl F. Roser 5-15-78 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CHERRY VALLEY TOWNSHIP
LAKE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET