## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN-: -	CORNER CODE NUMBER	
	1. PUBLIC LAND SURVEY.	T. 18 N. R. 12 W.	_Н-10	
	2. PROPERTY CONTROLL- 22 ING IN SECTION—22-	,T. 18 N. R. 12 W.	12; 16	
	3. MISCELLANEOUS PROPERTY IN SECTION 27	,T18 _ N. R12 _ W.	*646.2'-W of #9	
	4. LOT NO, RECORDED PLAT			
	5. PRIVATE CLAIMS		<u></u>	REGISTER OF DEEDS STAMP AND
	the corner points mentioned in line re-established, monumented, re-me and rules therefore as required in Bureau of Land Management or by and 5 above were, in a field survey	es 1 and 2 above were, in a commented, recovered or resthe current manual of survey a decree of a court of law.  onNovember_6,	tored as expressed below any instructions of the United Furthermore, that the corn 19_78, found, recovered, re	of P.A. 74, Michigan P.A. of 1970, r. 7 , 1978 , established, d in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 stored, established or re-established tration for Land Surveyors or, by a
	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	GAKKKKKKKKKKKKKKK	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
		9" B. Oak	e-rod w/RLS cap. N30°W 38.5' N45°E 41.9' /loc tag	
		Ctr. E-W dirt	Due N 33'	
		001, 2 // 0110		
H-10 12 16	B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  Established center of Sec. 27 at intersection of one-quarter lines.  Re-established S 1/8 Cor. on N-S 1/4 line of Sec. 22 per std. B.L.M. instructions.  Geo. Johnson's (1916) 1/8 Cor. (wagon tire iron) as noted in Wits., is over-grown solid by tree roots. Corner falls in old fence corner remains, N,S &E.  Fd. iron for 1/8 Corner per Geo. Johnson survey & Sec. Sub'n. of Sec. 22, Dec. 1916.  Also one Johnson Wit. still standing; B.Oak, S47°W, 32.7'.  Estab. NE Cor. of W 1/2- NW 1/4- SE 1/4 of Sec. 27, Per Std. B.L.M. instructions.			
	C. Description of monument for c H-10	orner and accessories establi		e position of the corner:
3" W.P 6" W.P Set Ce	5/8"X40" re-rod w/RLS ca line N10°W 19.5' line S30°W 46.3' d.Post w/Loc. Tag Due N 33' W dirt rd.	& Ced. Post w 11" W. Oak 15" B.Oak Fd. 1 1/2"X3/ S3	//Loc. Tag. N40°W 26.2" S20°W 1.8' '8" wagon tire iron 30°08'W 2.16'	wagon tire iron. 8" R.Pine N20°W 20.63' 5" W. Oak N55°E 4.76'
	SIGNED BY CALL 7.	Poser 5-23	3-79 DATE	Old Fn. Cor. (N-S&E)  Due W 15'
	SURVEYOR'S MICHIGAN REGIS	STRATION NO12028		CARL
	FOR STATE AND UNITED STA	TES AGENCIES:		LAND *3
	SIGNED BY	CHIEF OF SURVEY PARTY	DATE	No. 12023
	APPROVED AND SIGNED BY	MICHIGAN REGISTERED LAN	DATE_	(SEAL)
			T 5.1	ERRY VALLEY TOWNSHIP KE COUNTY
	SURVEYOR'S MICHIGAN REGIS	STRATION NO		