Lake Ca.

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN -:	CORI	NER CODE NUMBER	
	1. PUBLIC LAND SURVEY.	. T. 18 _ N. R1	K-6;	К-7	
	2. PROPERTY CONTROLL-14 ING IN SECTION: 14	.,T. 18 %, R1	3_ w: 14;		
	3, MISCELLANEOUS PROPERTY IN SECTION	.,T	E. W.		
	4. LOT NO.	ORDED PLAT	······································		
	5, PRIVATE CLAIMS.			-	REGISTER OF DEEDS STAMP AND FILING NUMBER
Carl F. Roser , do hereby certify that under requirent the corner points mentioned in lines 1 and 2 above were, in a field survey on re-established, monumented, re-monumented, recovered or restored as expressed below and rules therefore as required in the current manual of survey instructions of the Un Bureau of Land Management or by a decree of a court of law. Furthermore, that the and 5 above were, in a field survey on, 19, found, recovere as expressed below and in conformance with the rules of the Michigan State Board of Decree of a Court of law:					e 14, 19.78 _, established, d in conformance with regulations States Department of the Interior, or points mentioned in lines 3, 4 stored, established or re-established
	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	zwenkakan kan nan	HARRIKARIAN 16	xoxitoxexxx	
		6" B.Oak	5/8"X18" ree N4:	5°W 57.2'	
		5" W.Oak Set Ced.Po	st w/Loc.	0°E 48.8† Tag e N 33†	
			st (Fn.W&S) Bit.Rd. Du	Due S 32*	
K-6 K-7 14	B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: Fd. 1/2"X1/2" Sq. Iron in ctr. of N-S Bit. surfaced road. Corner fits two Geo. Johnson Wits. dated April 10, 1928. Ctr. of dirt road to east is North, 14+. Fd. 3/4" Ir. rod that fits Blass Wits. & has been used by Clint Cole for Cert. Survey. Corner fits two Geo. Johnson Wits. (1928). Fd. 3/4" pipe that fits 1/8 corner position mid-way & on line between 1/4 Cor. to N. and Sec. Cor. to S. Cor. Fn. post, down, fn's. E&S, is 17'-N & 33'-E. Re-established 1/8 Corner mid-way and on line between Sec. Cor. to E & 1/4 Cor. to W. Strong Mag. "pull" (not dug-out) about 2.5'-N.				
	C. Description of monument for K-6	ceorner and accessorie	s established to K-7	perpetuate locating th	ne position of the corner:
7" R. 16" R.	'2"X1/2" Sq. Iron, Pine S50°E 38.81'	Fd. 3/4" in Rd. interse 12" B. Oak 1 1/4" pipe	on rod in l	5" 77.9' 5"	. 3/4"X18" pipe W.Oak N30°W 38.4 Swp.W. Oak S65°W 42.0 t Ced.Post w/Loc. Tag Due W 33'
(scrib	7.0ak S56°W 47† ne Stp.	Set Ced.Pos	st w/Loc. Ta N45°W	ag Ct	r. N-S Bit.Rd. Due E 1'+ r. dirt rd. easterly Due N 49'+
·	SIGNED BY Cal 7.	Roces 3-	27-79	DATE	OF MICKING
	SURVEYOR'S MICHIGAN REC	GISTRATION NO.	12028	-· -	CARL 2
	FOR STATE AND UNITED ST				SURVEYOR No. 12028
	SIGNED BY.	CHIEF OF SURVEY PARTY		DATE	- TANGE CHANGE STANK
	APPROVED AND SIGNED BY	MICHIGAN REGIE	TERED LAND BURYE	DAIE.	(SEAL)
	SURVEYOR'S MICHIGAN REC	STRATION NO			EBBER TOWNSHIP AKE COUNTY
	50 NATION S MICHIGAN REC	SISTEMBLION NO	 -		