## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

1. PUBLIC LAND SURVEY	
ING IN SECTION, T	
4. LOT NO, RECORDED PLAT	
I,CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on	
I,	
I,	
the corner points mentioned in lines 1 and 2 above were, in a field survey on 4/15, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:  **Exxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	
C. (CONT). E-7  FD 3/8" PIPE W/RLS CAP & NARROW FD 1 1/4" PIPE.  GAUGE R.R.RAIL. 6" MAPLE N60°W 46.74	
C. (CONT). E-7  FD 3/8" PIPE W/RLS CAP & NARROW FD 1 1/4" PIPE.  GAUGE R.R.RAIL. 6" MAPLE N60°W 46.74	
GAUGE R.R.RAIL. 6" MAPLE N60°W 46.74	
7011 14015	
7 11.148 8 11.5111	
24" MAPLE S50°E 37.65 5" R OAK S35°E 41.40	
SET CED POST  W/LOC TAG  N45°E  47'  W/LOC TAG.  DUE F 33'	
., === ., Dol E .,	
CTR N-S DIRT RD DUE W //'± CTR N-S DIRT RD DUE E 2'± CTR E-W DIRT RD DUE N 4'±	
K-4 FD "T" IN CTR OF BIT RD INTERSECTION N-S-W AND IN LINE WITH CTR OF GRAVEL RD EAST.  I-4 FD 1" IRON THAT FITS KILGORE ESTATES PLAT.  E-6 FD 1 1/4" PIPE THAT FITS PREVIOUS SURVEY BY RLS, J. WILCOX AND ONE OLD GEO. H.  JOHNSON WIT. OLD FN COR (FNS N-S-E) IS 31'E & 5'S.  E-7 FD 3/8" PIPE OVER OLD R.R. RAIL BURIED IN DIRT RD INTERSEC. COR USED BY RLS,  J. WILCOX, IN 1977.  E-5 FD 1 1/4" PIPE; PREVIOUSLY USED RLS'S, GEO. BLASS & J. WILCOX. COR FITS ONE OLD  GEO. H. JOHNSON WIT.	
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:	
K-4 I_4 F_6	
FD 3/4" X 3/4" "T" IRON. FD 1" ROUND IRON (FLUSH). FD 1 1/4" PIPE.	
POWER POLE N10°W 118.65 POWER POLE \$30°E 68.41 16" MAPLE N25°W 68	.73
12" TWIN BEECH N50°E 82.62 21" B CHERRY S60°W 63.96 10" B CHERRY N55°E 32 SET CED POST 2" R PINE N50°E 99.51 12" MAPLE S25°E 17	.45
W/LOC TAG. N45°E 66' SET CED POST SET CED POST	.01
W/LOC TAG DUE S 33' W/LOC TAG. DUE E 33	t
CTR E-W BIT RD DUE N 3'± CTR N-S DIRT RD DUE W 8':	<u>t</u>
CTR GRAVEL RD N DUE E 41±	
Of MICKING	
SIGNED BY COLL T. ROSEN 03-08-82 DATE	
SIGNED BY CALL 7. Poser 03-08-82 DATE  SURVEYOR'S MICHIGAN REGISTRATION NO. 12028  CARL F. ROSER LANGEL SURVEYOR	
FOR STATE AND UNITED STATES AGENCIES:  SURVEYOR  NO.	
12028	
SIGNED BY DATE DATE CHIEF OF BURVEY PARTY	
MICHIGAN REGISTERED LAND SURVEYOR	
(SEAL)	
ELLSWORTH TWP	
SURVEYOR'S MICHIGAN REGISTRATION NOLAKE COUNTY	

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 26, 1971 REVISED MAY 14, 1975