LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
I, PUBLIC LAND SURVEY.	T. 19 N. R. 11 W.	J−2, K−3	
2. PROPERTY CONTROLL. 2 ING. IN SECTION————————————————————————————————————	,T. 19N N. R. 11 W.	16,15,5	
3. MISCELL ANEOUS PROPERTY IN SECTION			
4. LOT NO , RECO	RDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in line re-established, monumented, re-mand rules therefore as required in Bureau of Land Management or and 5 above were, in a field surve	nes 1 and 2 above were, in a nonumented, recovered or real the current manual of survival decree of a court of law you	field survey on	of P.A. 74, Michigan P.A. of 1970, ————————————————————————————————————
<i>жинали</i> ликихихих	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		
C. CONTINUED: *5 SET 5/8"X34" RE-ROD & CED PO 4" SUG MAP (IN CLUMP 10) N30 6" SUG MAP S20 5" SCOTCH PINE DUE FN COR N-S & E-W S43 N-S FN DUE E-W FN FT. DUE \$5 NE COT. of SE 14-NW 14 of S45	PE 12.8 2 PW 29.1 1 W 34.2 1 P18'W 32' 5	K-3 TD PK;REPLACED W/ 3/4 14" W PINE 3" CEDAR O" CEDAR SET CED POST W/LOC TAG	X18" PIPE. N80°W 46.27 N25°E 85.55 S45°W 60.25
B. Description of corner evidence		lied in restoring or re-establishi	ing corner:
16 FD. G. BLASS "T" IRON MI PIPE AT OLD STANDING FN. 15 ESTAB. 1/8 COR MIDWAY & 5 ESTAB 1/8 COR AT PRO-RAT J-2 ESTAB CTR OF SEC. 2 AT I K-3 FD "PK" IN CTR N-S Bit SU LINE W/OLD FN TO WEST.	COR. (FN, LINES E 8 ON LINE BETW THE SW ED DIST TO US,(G.L.(NTERSECTION OF ONE—(SS) IS 3'±N, & 3'±E, COR & S 1/4 COR, OF S), PLAT) BETW THE CTR WUARTER LINES.	& THE N1/4 COR OF S-2.
C. Description of monument to	corner and accessories estat	dished to perpetuate locating th	he position of the corner:
16 FD & ACCEPTED "T" IRON, FLUS W/BLASS SURVEY TAG; ADDED CED POST W/LOC TAG. 20" W PINE N80°W 34.25 18" W PINE N15°E 21.99 10" CEDAR S35°W 22.62	H, SET 5/8X34" RE-RO POST W/LOC TAG. 13" MAPLE (IN CLUM 8" CHERRY OLD N-S FN REMAIM	15 DD W/RLS CAP & CED MP 3)N5°W 89.8 S45°W 40.0 NS DUE E 2'±	J-2 SET 5/8"X34" RE'ROD W/RLS CAP & CED POST W/LOC TAG. 11" SUG MAP N35°W 13.8 9" SUG MAP \$30°E 23.3 16" SUG MAP \$30°W 10.5
			AND MANAGEMENT
SIGNED BY Cal 7. SURVEYOR'S MICHIGAN RE	GISTRATION NO 1202	8	CARL F. ROSER LANDEAL) SURVEYOR NO. NO.
FOR STATE AND UNITED S		15490	No. 12028 AND SURFIELD
SIGNED BY	CHIEF OF SURVEY PARTY	DATE	
APPROVED AND SIGNED BY	MICHIGAN REGISTERED	LAND SURVEYOR	(6EAL)
		1.41	LSWORTH TWP KE COUNTY
SURVEYOR'S MICHIGAN RE		···	
FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975			

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET