LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. ●, R. 11 ●. W.	H-1; H-2; H-3
2. PROPERTY CONTROLLING IN SECTION 3	T. 19 N. ●, R. 11 ●. W.	9
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 03, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. CONTINUED: 9

FD 3/4" X 24" PIPE;ADDED RLS CAP & CED POST W/LOC TAG.

8" SUGAR MAPLE	N80°W	3.2'
3" W BIRCH	N15°E	28.8'
8" SUGAR MAPLE	DUE E	18.8'
CONC PLAT MON	S24°41'E	29.77'
CTR N-S DIRT RD	DUE W	56'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H-2 ESTAB. CTR. OF SEC.3 AT INTERSECTION OF ONE-QUARTER LINE'S.

H-1 FD.1" PINCH PIPE AS SET BY CONS. POWER CO. SURV., F.A.FISHER, JUNE 23, 1936,F.B.#311, FOR N1/4 COR. OF SEC.3. THE S1/4 COR. OF SEC.34 (T20N-R11W) IS S89°59'W, 55.41.

H-3 FD. & ACCEPTED 4" ROUND CONC. MONUMENT FOR S1/4 COR. OF SEC.3. FITS 3-BLASS OR COLE WITS

9 FD. & ACCEPTED 3/4" X 24" PIPE FOR SW COR. OF SE1/4 OF FRL. NE 1/4 OF SEC.3;MAY HAVE BEEN SET BY G.H.JOHNSON. A CALC. 1/8 COR. POSITION WOULD BE 1.0'-S. & 0.2'-W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-1

FD. 1" PINCH PIPE & RAISED TO SURF. W/1/2" X 40" PIPE.

10" R. PINE	S20°E	52.68'
10" R. PINE	S35°W	47.16'
S 1/4 34	S89°59'W	55.41'
SET CED POST W/LOC TAG	DUE S	40'
CTR E-W DIRT RD	DUE S	11'

H-2

DROVE 5/8" X 34" RE-ROD W/RLS CAP & CED. POST W/LOC TAG.

6" SUGAR MAPLE	N10°W	19.4'
8" SUGAR MAPLE	N30°E	10.1'
11" SUGAR MAPLE	S85°W	23.8'
FD CO. PO. CO. IRON	S21°33'E	56.48'
ELY EDGE PINE RV	DUE W	116'

H-3

FD 4" RD CONC MON W/1/2" RE-ROD;ADDED CED POST W/LOC TAG.

7" R OAK	N70°E	20.10'
11" SUGAR MAPLE	S55°E	56.28'
4" R OAK	N15°W	10.25'
CTR E-W DIRT RD	DUE S	9'
FD IRON/W CO PO CO CAP	DUE S	32.9'

SIGNED BY Carl F. Roser 6-19-84 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

ELLSWORTH TOWNSHIP
LAKE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14 1975

MAY PLACE SKETCH ON BACK OF ATTACHED SHEET