LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N., R. 11 W.	J-1, K-1, K-2
2. PROPERTY CONTROLLING IN SECTION 3	T. 19 N., R. 11 W.	10
3. MISCELLANEOUS PROPERTY IN SECTION 3	T. 19 N., R. 11 W.	⁜658.6'-S of G-2.
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 4/8, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 4-15, 1981, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONT.)

K-2

FD 3/4" PIPE (FLUSH) IN CTR BIT RD.

11" W PINE	N50°W	67.8
12" R PINE	S60°W	76.5
12" SUG MAP	N50°E	116.8
SET CED POST W/LOC TAG	DUE W	33'

⁜

SET 5/8"X34" RE-ROD W/ RLS CAP & CED POST W/LOC TAG.

7" W PINE	N10°W	5.9
5" W PINE	S75°E	17.7
CTR N-S TRAIL	DUE E	28'

10

SET 5/8"X34" RE-ROD W/RLS CAP & CED POST W/LOC TAG.

21" R PINE	N60°E	6.0
4" R PINE	S 5°E	6.1
3" W PINE	N65°W	10.8
CTR N-S TRL	DUE E	24'±

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-1 FD 1/2" PIPE IN APPROX CTR OF E-W GRAVEL RD. A FN COR N & E IS 21'-W & 30'-N.

K-1 FD 5/8" IR ROD BY RLS, CLINT COLE. COR FALLS IN APPROX CTR OF E-W GRAVEL RD; IS IN LINE W/CTR OF B.TOP RD TO SO & IS 13'±E OF CTR OF B.TOP RD TO N. THE SE COR OF SEC. 35 T20N-R11W, FD 1 1/4" PIPE (RAISED W/ 3/4" X 8" PIPE) IS N86°25'W, 18.73'.

K-2 FD 3/4" PIPE IN CTR OF N-S BIT. SURFACE RD. FITS G.H. JOHNSON WITS.

⁜ ESTAB. NW COR OF S1/2 - N1/2 - SW1/4 OF SEC. 3 PER STD B.L.M. INSTRUCTIONS.

10 ESTAB. 1/8 COR MID-WAY & ON LINE BETW W1/4 COR & SW COR OF SEC. 3.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

J-1

FD 1/2" PIPE (BURIED 1').

12" R PINE	N10°W	56.08
10" R PINE	N40°E	71.10
SET CED POST W/LOC TAG	DUE S	33'
FN COR S & E	DUE S	42'

K-1

FD 5/8" IR ROD; RAISED W/ 1"X9" PIPE.

27" MAPLE	N15°E	107.10
POWER POLE	S65°E	117.00
4" R PINE	S35°E	82.02
SET CED POST W/LOC TAG	S45°W	55'

SIGNED BY Carl F. Roser 03-2-82 DATE

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

ELLSWORTH TWP
LAKE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET