LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.	T. 19 N. S., R. 11 E. W.	E-2, F1, F3
2. PROPERTY CONTROLLING IN SECTION 4	T. 19 N. S., R. 11 E. W.	15, 16
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 4/15, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. (CONT)

15			16		
FD 1/2" IRON ROD W/RLS CAP			SET 3/4" X 22" PIPE.		
6" W PINE	N40°W	99.70	4" R PINE	N65°E	62.49
5" R PINE	N70°E	103.95	POWER POLE	S 5°E	71.84
FD OLD 1" PIPE	S10°E	7.4'	FD OLD 1 1/4" PIPE	S 5°W	6.90
SET CED POST	DUE N	33'	SET CED POST		
W/LOC TAG			W/LOC TAG.	DUE N	33'
CTR E-W DIRT RD	DUE S	5'±	CTR E-W DIRT RD	DUE S	7'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-2 FD. 4" CONC MON; NE COR OF PLAT OF "PINE RIVER WOODS". MON. FITS 3 - RLS, CLINT COLE WITS. COR IS 120'± EAST OF IRREGULAR N-S BIT. RD.

F1 FD 1" PIPE THAT FITS 3 - RLS, CLINT COLE WITS; PIPE IS AT OLD FN COR S & E. A FD OLD FN. COR N & W IS EAST, 116'±.

F3 FD 3/4" IRON ROD AS RECOVERED & ACCEPTED BY RLS, CLINT COLE IN 1977.

15 FD 1/2" ROD BY RLS- CLINT COLE ALONG SIDE "T" IRON BY G.BLASS. COR IS IN LINE WITH OLD FN REMAINS NORTHERLY.

16 ESTAB 1/8 COR MID-WAY & ON LINE BETW S 1/4 COR & SE COR OF SEC. 4. COR IS IN LINE WITH OLD FN REMAINS NORTHERLY ON GROUND.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-2			F1			F3		
FD 4" ROUND CON MON ADDED;			FD 1" PIPE; ADDED CED POST W/			FD 3/4" IRON ROD		
CED POST W/LOC TAG			LOC TAG.			11" R PINE	N35°W	43.72
7" & 12" MAP	N 5°E	68.20	13" B CHERRY	N25°E	11.32	6" R PINE	S10°W	56.42
9" MAPLE	N75°E	37.75	8" HORN BEAM	S30°E	51.40	13" R PINE	S35°W	75.06
5" R. PINE	S45°W	47.72	6" W PINE	S35°W	35.15	SET CED POST		
FD CONC MON	N85°W	64.8'	N EDGE PINE RV	DUE S	94'±	W/LOC TAG	DUE N	33'
						CTR E-W DIRT RD	DUE S	12'

SIGNED BY Carl F. Roser 03-02-82 DATE

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

ELLSWORTH TWP
LAKE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET