LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. R. 11 W.	F-4, H-5, H-4, J-4
2. PROPERTY CONTROLLING IN SECTION 11	T. 19 N. R. 11 W.	5
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 13, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONTINUED)

~~XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX~~

H-4

FD 1" X 1" T IR BURIED 2".
8" SUG MAPLE N25°E 44.86
11" SUG MAP N50°W 69.90
P POLE S10°E 75.28
CTR E-W BIT RD DUE S 2.5'
SET CED POST W/LOC tag
BESIDE FD CONC
PLAT MON DUE N 33'

J-4

FD BOAT SPK BURIED 2".
32" SUGAR MAPLE N65°W 77.00
10" SUGAR MAPLE S50°E 76.78
13" SUGAR MAPLE DUE S 42.55
SET CED POST W/LOC TAG
BESIDE FD CONC MON. DUE N 33'
CTR E-W BIT RD DUE S 5 1/2'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

F-4 FD & ACCEPTED 1/2" PIPE FOR CTR OF SEC 9 PER GOURDIE-FRASER CERT OF SURVEY; LIBER 01, PG 448.

H-5 RESTORED S 1/4 COR OF SEC 10 ON LINE BETW THE SE & SW COR'S OF SEC 10 & ON LINE ACROSS FD. CTR & N 1/4 OF SEC 10; PER PREVIOUS BLASS SURVEY'S IN SEC 10 (N 1/4 COR & CTR).

H-4 FD & ACCEPTED 1" X 1" T-IR FOR CTR OF SEC 10; PER PREVIOUS BLASS SURVEY'S IN N 1/2 OF SEC 10.

J-4 FD & ACCEPTED BOAT SPK FOR CTR OF SEC 11 AS ESTAB BY BLASS AT INTERSEC OF ONE-QUARTER LINES IN 1966.

5 ESTAB SE COR OF NE 1/4 OF NW 1/4 OF SEC 11, MID WAY & ON LINE BETW RECOV CTR & N 1/4 COR OF SEC 11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

F-4

FD 1/2" PIPE FLUSH
P POLE DUE S 34.63'
8" TRIPLE MAP N45°W 103.50'
SET CED POST
W/LOC TAG DUE S 33'
CTR E-W BIT
RD. NORTH 0.5'

H-5

SET DNR MON & CED POST
5" SUG MAP DUE N 22.0'
7" SUG MAP N30°E 43.1'
4" W PINE S20°W 61.3'
CROOKED DUE S 28'+2'
E-W FN

5

SET 5/8" X 34" REROD W/RLS CAP
& CED POST W/LOC TAG.
4" SUG MAP N60°E 17.1'
11" SUG MAP S55°E 20.5'
6" R OAK N70°W 15.6'
FD OLD 1"PIPE
AT COR OF FN
W & S. N87°31'W 14.34

SIGNED BY Carl F. Roser 6-19-84 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

(SEAL)

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

ELLSWORTH TWP
LAKE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET.