LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N., R. 11 W.	G-7, F-7, G-6
2. PROPERTY CONTROLLING IN SECTION 16	T. 19 N., R. 11 W.	1, 7
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6/2/, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONT).

1

SET 5/8"X34" RE-ROD W/RLS CAP & CED POST W/LOC TAG.

3" R OAK	N70°E	11.2'
7" R PINE	S40°W	17.6'
9" R PINE	S70°W	27.9'

7

SET 5/8"X34" RE-ROD W/RLS CAP & CED POST W/LOC TAG AT OLD FN COR.

4" W PINE	S50°E	39.2'
6" BEECH	S15°W	13.8'
FD MKD 30" W PINE STP.	N20°W	10.0'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-7 FD & ACCEPTED 1/2"X18" ROD BY RLS, J. GRAY. COR SET FROM OCCUPANCY. 33' N OF FENCE CORNER, FN'S S & W.

F-7 FD & ACCEPTED 1 1/4" PIPE FOR S1/4 COR. SEC. 16. WIT TREES (W/NAILS) ALREADY USED BY OTHERS - PROBABLY RLS, J. GRAY. AN OLD FENCE CORNER, FN'S E-W-S, IS 32'S & 4'W. CTR OF E-W DIRT RD ON CURVE AROUND HILL IS DUE NORTH, 63'±.

G-6 RESTORED E1/4 COR. SEC. 16 FROM G.H.JOHNSON WIT, MKD PINE STP., N80°W, 11'. 1/4 COR FITS N1/8 ON E LINE OF SEC. 16; (1' W OF LEANING FENCE CORNER).

1 ESTAB W1/8 COR ON N LINE OF S-16; MIDWAY & ON LINE BETW THE NW COR & N1/4 COR OF S-16.

7 ESTAB N1/8 COR ON E LINE OF SEC. 16; MIDWAY & ON LINE BETW NE COR & E1/4 COR OF S-16. OLD LEANING FN CORNER IS 1' E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7

FD 1/2"X18" RE-ROD W/RLS CAP; ADDED DNR MON & CED POST.

28" MAPLE	DUE E	64.55
19" R OAK	S10°E	42.12
3" W ASH	S60°W	31.45
FN COR S & W	DUE S	33'

F-7

FD 1 1/4" PIPE; ADDED CED POST W/LOC TAG.

23" R OAK	N 5°W	16.06
12" BEECH	S10°W	16.52
8" MAPLE	S75°W	21.14

G-6

SET DNR MON & CED POST.

3" R OAK	N 5°E	16.1'
2" W PINE	S35°W	37.8'
2" W PINE	N80°W	15.8'
OLD 32" W PINE STP	N80°W	11'

SIGNED BY Carl F. Roser 03-08-82 DATE

STATE OF MICHIGAN — CARL F. ROSER LAND SURVEYOR No. 12028 (SEAL) — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

ELLSWORTH TWP,
LAKE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET