LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	COR	NER CODE NUMBER		1
1. PUBLIC LAND SURVLY	r. 20 🎳 R.;	// ₩. E-12	ستر E−11 و ?		
2. PROPERTY CONTROLL- ING IN SECTION-	32 ,1 20 № ., k	11 8: .7		i ! !	
3, MISCELLANEOUS PROPERTY IN SECTION	$T_{\mathcal{S}} = \{ 1, \dots, N_{\mathcal{S}} \mid B_{\mathcal{S}} \}$. W. L.		•	
4, 1.04 NO , Ris	ORDED PLAT			 	
5. PRIVATE CLAIMS				REGISTER OF DEED FILING NU	-
I, CARL E. ROSER the corner points mentioned in re-established, monumented, re and rules therefore as required Bureau of Land Management o and 5 above were, in a field sur as expressed below and in conf Decree of a Court of law: B. (CONTINUED) XXXMXXMXMXXXXXXXXXXXXXXXXXXXXXXXXXXXX	lines I and 2 above we smonumented, recovered in the current manual reby a decree of a court vey on.	re, in a field sur d or restored a of survey instru- of law. Furthe , 19 of the Michigan	vey on MARCH is expressed below and actions of the United Structure, that the corner found recovered, rest. State Board of Registr	5	t., established, lith regulations of the Interior, in lines 3, 4 r re-established
E-11 COULD FIND NO PHYS				ON LINE & DB	L. DISTANCE
ACROSS RECOVERED 1 111.10' (NO EVID O AT 110.40'. BLASS CTR OF DIRT RD EAS	/8 COR & 1/4 COR F BLASS NAIL.) W - W.P., S45°W, FA	TO EAST. (E FIND THIS S BEEN TIPP	G.BLASS HAD B.T. 25" W.P., S50°E ED OVER. CTR OF	IN 1951, 8" , AND SET SID M-S BIT RD 1	W.P., S54°E, E NAIL IN TREE
9" R PINE SO5°E	OF SEC 33 PER ''I JLD; COLUMBUS, OI BOUND COR'S- RI MON)- G.H.JOHN S-33, ''CONC POS' BUT A 24" PINE 36" RD IRON PIN G.H.J.) CALL FOI 1'±-S & 4'-E. Come corner and accessorie T. FD 1' 49.54' CED I 45.65' 10" I 177.80 6" I 24' 11" I	MAP OF SURVE HIO-MORRIS EC. 1751- W SONS CO. SUF I'', PINE 241 STUMP IS SO FOR NE COR R IRON PIN. OR IS ON LIM I' X 361 ROUS POST W/LOC R PINE B CHERRY R PINE	EY" OF S 1/2 OF I. TOWNSEND- FEB LY OF #5 (FD CO RVEYOR NOTES FOR L S66°30'E 194.5 66°E 195'± TO 1/ OF SE 1/4 OF NE COR IS IN LINE NE WITH N'LY EDG perpetuate locating the	S-33; "FROM SE . 1948, LUTHEL NO MON) & REC S-33 (AUG 19: '. THE CONC L 4 COR AS RESTO 1/4 OF S-32. WITELEN. TO ME E OF NEW FN. position of the cor E-11 DROVE 5/8" X W/RLS CAP. 4" TW CED 9" R PINE	R, MICH.": 545.0'- 28) SHOW POST IS DRED ABOVE. OLD CO. WEST (*1'). TO EAST. 04" RE-ROD N45°W 42.37 S60°W 57.10 S50°E 110.40
SIGNED BY Carl?. A SURVEYOR'S MICHIGAN REFOR STATE AND UNITED S	GISTRATION NO		DATE	F. I	F M/C
SIGNED BY	CHIEF OF SURVEY PARTY		L L DATE .		
APPROVED AND SIGNED B	Y	TERED LAND SURVE	DATE.		· ·
	MICHIGAN REGIE	TERED CAND SURVEY	I UR	(SEAL)	
SURVEYOR'S MICHIGAN RE	GISTRATION NO.			DOVER TWP LAKE COUNTY	

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975