LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 20 N. S., R. 11 E. W.	F-11, F-12
2. PROPERTY CONTROLLING IN SECTION 33	T. 20 N. S., R. 11 E. W.	1, 5, 12
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 5, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONTINUED)

5

DROVE 5/8" X 34" RE-ROD W/RLS CAP & CED POST W/LOC TAG.

9" B. CHERRY	N25°W	69.28
2" W PINE	DUE E	19.32
2" W PINE	S10°E	8.00
OLD N-S FN REMAINS	WEST	2'±
OLD FN REMAINS E'LY ON GROUND	SOUTH	75'±
NEWER QUICKIE FN W & S	SOUTH	58'±

12

FD OLD 1" PIPE; ADDED RLS CAP & CED POST W/LOC TAG.

7" SUG MAPLE	N85°E	29.8
3" SUG MAPLE	S05°W	14.6
14" B CHERRY	N30°W	13.2

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

F-11 FD & ACCEPTED OLD PLOW POINT IN LINE WITH FN S'LY & IN APPROX CTR OF E-W DIRT RD, FOR N 1/4 COR OF S-33.

F-12 FD & ACCEPTED OLD 1" PIPE & 1- G.H.JOHNSON WIT. (LG GRANIT STONE NW THAT HAS RECENTLY BEEN SKIDDED NE'LY) FOR CTR OF S-33. NEW N-S 1- STRAND B-W ON 1 1/2" STEEL PIPE POSTS IS WEST, 3'.

1 FD PLOW POINT (BURIED 10"), IN CTR OF E-W DIRT RD, FOR W 1/8 COR ON N LINE OF S-33.

5 ESTAB NW COR OF SW 1/4 OF NE 1/4 OF S-33 MID-WAY & ON LINE BETW FD N 1/4 COR & CTR OF S-33.

12 FD & ACCEPTED OLD 1" PIPE FOR SW COR OF NW 1/4 OF SE 1/4 OF S-33. COR IS AT OLD FN COR (FN'S N&E) & FITS 1- G.H.JOHNSON WIT.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-11

FD PLOW POINT IN CTR E-W DIRT RD.

4" R PINE	S40°E	54.24
7" B CHERRY	S15°W	29.81
P POLE	N10°E	51.89
SET CED POST W/LOC TAG	DUE S	33'

F-12

FD OLD 1" PIPE; ADDED CED POST W/LOC TAG.

12" W PINE	N40°W	58.3
CTR 24" X 40" ROCK	N05°W	63'
12" R PINE	N30°E	47.9
OLD N-S FN REMAINS	DUE W	8'±2'

1

FD PLOW POINT IN CTR E-W DIRT RD.

9" R PINE	N50°E	48.52
5" W PINE	S35°E	37.44
3" W PINE	S35°W	35.63
SET CED POST W/LOC TAG.	DUE S	33'

SIGNED BY Carl F. Roser 6/07/84 DATE

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

DOVER TWP
LAKE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET