## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCAT	IED IN-:	CURNE	R CODE NUMBI			
	I, PUBLIC LAND SURVEY	т. 20_	N. R. <u>12</u>	<u>₩</u> : <u>M-'8; M</u> -	-6; M-7; I	-6		
	2. PROPERTY CONTROLL- ING IN SECTION—	,Т	N. S., R	E. W				
	3. MISCELLANEOUS PROPERTY IN SECTION =	Т.	N. S., R.	F.				
	4. LOT NO	ECORDED PI	.AT		···-			
	5. PRIVATE CLAIMS				<u> </u>			EEDS STAMP AND
	I, CARL F. ROSER		da herel	ny certify that a	nder reanirem	ients of	PA 74 Mich	igon P A of 1970
	the corner points mentioned i re-established, monumented, and rules therefore as require Bureau of Land Management	in lines I and re-monument ed in the curr or by a decr	2 above were, sed, recovered or manual of see of a court of	in a field survey or restored as e survey instruction law. Furthermo	on	UNE 29 w and in ited Stat corner p	19 n conformance tes Departmen points mention	_81_, established, e with regulations nt of the Interior, ned in lines 3, 4
	and 5 above were, in a field s as expressed below and in co							
	Decree of a Court of law:	morninge w	THE THIRD OF	ine memgan or	nte izonte en .			
C. C	ONTINUED			***************************************				
	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	<i>XXXXXXXXXXXXX</i> XXXXX	XXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	жжжжжж 1-6			
	ONR MON & CED POST				10N & CED	POST		
9" M		N65°E	33.96'	8" W. OA		0°E	22.5'	
	. PINE N END 12" CONC CULV	S60°W S80°W	80.92' 9.0'	4" W. PIN 7" W. OAK		eom 0oM	7.3' 22.7'	
	N-S BIT RD ON CURVE	DUE W	33'	N-S RAND		E E	4.3	
	B. Description of corner evid FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2"	1 1/4" X • X 36" FL	20" CHANNE ATTENED RUS	IL IRON FOR	E 1/4 COR	NER OF	SEC 24.	
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  S SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4  COR OF S  For corner at	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W nd accessories e	IL IRON FOR  ITY PIPE W/T  I. CORNER 1  IE STUMP B.T  24, T20N-F  CORNERS 1/2  IAY & ON LIN  stablished to per  FD 2 1/2  14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO WE BETWEEN TPETRIALE TO THE BETWEEN TO THE BETWEEN TO THE BETWEEN THE BETWEE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ng the p M-6 E W/TW 35°E	SEC 24.  SINSIDE   OLD FENCE  \$ 19, T20  \$ SOUTH.  SE & SE COllosition of the 45.38'	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner:
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO WE BETWEEN Toctuate locati X 36" PIP WE N	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO WE BETWEEN Toctuate locati X 36" PIP WE N	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO WE BETWEEN Toctuate locati X 36" PIP WE N	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO THE BETWEEN TREATMENT TO THE BETWEEN THE BETWE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO THE BETWEEN TREATMENT TO THE BETWEEN THE BETWE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO THE BETWEEN TREATMENT TO THE BETWEEN THE BETWE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO THE BETWEEN TREATMENT TO THE BETWEEN THE BETWE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  E SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4 I  COR OF S  Hor corner at  ANNEL IRO	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N;	TY PIPE W/T CORNER 1 CORNER 1 24, T20N-F CORNERS 1/2 AY & ON LIN stablished to per 14" W. PIN	E 1/4 COR TWO 1" TIR IS IN LINE T. REMAINS R12W & SEC MILE TO THE BETWEEN TREATMENT TO THE BETWEEN THE BETWE	NER OF E IRON WITH N.E. 'S 18 NORTH THE N ING the P M-6 E W/TW	SEC 24.  SINSIDE TO COLD FENCE  \$ 19, T200 \$ SOUTH.  NE & SE COlorsition of the 45.381	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH) . MAPLE PHONE POLE N-S BIT TOP RD CED POST W/LOC TAG  SURVEYOR'S MICHIGAN IN FOR STATE AND UNITED SIGNED BY	1 1/4" X  X 36" FL  & SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4  COR OF S  for corner at  ANNEL IRO  S55°E 6  N65°E 6  EAST 1  EAST 5  REGISTRATIO  STATES AC	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N; 3.25' 0.14' 8' 0'  O4-OG ION NO GENCIES:	TY PIPE W/TO CORNER TO 24, T20N-F CORNERS 1/2 PIPE W/TO CORNERS 1/2 PIPE PIPE PIPE PIPE PIPE PIPE PIPE PIP	E 1/4 COR TWO 1" TIR IS IN LINE T, REMAINS R12W & SEC P MILE TO WE BETWEEN TPETUATE locati X 36" PIP WE S WE S WE S WE S WE S WE D WE D WE DATE	NER OF E IRON WITH NOR THE P M / THE P E SO E E SO E UE E SO E E	SEC 24.  IS INSIDE OLD FENCE  \$ 19, T201 \$ SOUTH.  IE & SE COlosition of the  NO 1" TIRE 45.38' 24.00' 37.68' 13' 33'  OF M/C/ ROSER BURVEYOR 12028	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH)	1 1/4" X  X 36" FL  & SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4  COR OF S  for corner at  ANNEL IRO  S55°E 6  N65°E 6  EAST 1  EAST 5  REGISTRATIO  STATES AC	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N; 3.25' 0.14' 8' 0'  O4-OG ION NO GENCIES:	TY PIPE W/TO CORNER TO 24, T20N-F CORNERS 1/2 PIPE W/TO CORNERS 1/2 PIPE PIPE PIPE PIPE PIPE PIPE PIPE PIP	E 1/4 COR TWO 1" TIR IS IN LINE T, REMAINS R12W & SEC P MILE TO WE BETWEEN TPETUATE locati X 36" PIP WE S WE S WE S WE S WE S WE D WE D WE DATE	NER OF E IRON WITH NOR THE P M / THE P E SO E E SO E UE E SO E E	SEC 24.  IS INSIDE OLD FENCE  8 19, T201 8 SOUTH.  NE 8 SE COI sosition of the  VO 1" TIRE 45.38' 24.00' 37.68' 13' 33'  CARL ROSER BURVEYUR 12028	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE
M-8 M-6 M-7 I-6 FD 1,	FD & ACCEPTED 1/2" X SET BY GORDON BONNEY FD & ACCEPTED 2 1/2" TO SEC 13, T20N-R12W & FITS PROBABLE GEO. RE-ESTABLISHED CORNE & ON LINE BETWEEN RE 1/8 LINE FENCES E & RE-ESTABLISHED E 1/4 C. Description of monument M-8 /2" X 1 1/4" X 20" CH D DNR MON (FLUSH) . MAPLE PHONE POLE N-S BIT TOP RD CED POST W/LOC TAG  SURVEYOR'S MICHIGAN IN FOR STATE AND UNITED SIGNED BY	1 1/4" X  X 36" FL  & SEC 18  JOHNSON  R COMM TO  COVERED OF  W AT 1/4  COR OF S  for corner at  ANNEL IRO  S55°E 6  N65°E 6  EAST 1  EAST 5  REGISTRATIO  STATES AC	20" CHANNE ATTENED RUS , T20N-R11W (1919±) PIN SEC'S 13 & NE-QUARTER MILE SOUTH. EC 15 MID-W and accessories e N; 3.25' 0.14' 8' 0'  O4-OG ION NO GENCIES:	TY PIPE W/TO CORNER TO 24, T20N-F CORNERS 1/2 PIPE W/TO CORNERS 1/2 PIPE PIPE PIPE PIPE PIPE PIPE PIPE PIP	E 1/4 COR TWO 1" TIR IS IN LINE T, REMAINS R12W & SEC P MILE TO WE BETWEEN TPETUATE locati X 36" PIP WE S WE S WE S WE S WE S WE D WE D WE DATE	NER OF E IRON WITH NOR THE P M / THE P E SO E E SO E UE E SO E E	SEC 24.  IS INSIDE OLD FENCE  \$ 19, T201 \$ SOUTH.  IE & SE COlosition of the  NO 1" TIRE 45.38' 24.00' 37.68' 13' 33'  OF M/C/ ROSER BURVEYOR 12028	FOR 1/4 COR COMM REMAINS TO EAST N-R11W MID-WAY CORNER FITS R'S OF S-15. corner: IRONS INSIDE