LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 20 N., R. 12 W.	I-2; I-3; J-3; K-3
2. PROPERTY CONTROLLING IN SECTION ____	,T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	

4. LOT NO. ____, RECORDED PLAT ____

5. PRIVATE CLAIMS ____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MAY 28, 19 81, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED

J-3

SET DNR MON & CED POST

6" MAPLE	N10°E	7.5'
6" MAPLE	S85°E	10.3'
3" MAPLE	S5°E	13.4'

K-3

SET DNR MON & CED POST

2-4" MAPLES	N45°W	16.6'
6" S. MAPLE	N05°W	49.8'
18" R. PINE	S15°W	51.4'
APPROX CTR 90'(±30') DIAM POT HOLE WITH STANDING WATER	S50°W	120' (±20')

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-2 RE-ESTABLISH W 1/4 COR OF SEC 2 BY SINGLE PROPORTION MEA. TO U.S. BETWEEN THE NW & SW COR'S OF SEC 2.

I-3 RE-ESTABLISH SW COR SEC 2 BY DOUBLE PROPORTION MEA. TO U.S.; 2-MILE EAST, 1 1/2 MILES WEST, 1-MILE NORTH & 1/2 MILE SOUTH TO RECOVERED CORNERS.

J-3 RE-ESTABLISH S 1/4 COR, SEC 2, EQUIDISTANT & ON LINE BETWEEN THE SE & SW COR'S OF S-2.

K-3 RE-ESTABLISHED SE COR OF S-2 BY DOUBLE PROPORTION MEA. TO U.S.; 1-MILE EAST, 2 1/2 MILES WEST, 1/2 MILE NORTH AND 1/2 MILE SOUTH TO RECOVERED CORNERS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2

SET DNR MON & CED POST

4" ASH	N55°E	16.7'
11" CEDAR	S60°E	26.6'
4" HEMLOCK	S45°W	20.5'
SW'LY EDGE PINE RV	DUE E	145' (±15')
SW'LY EDGE PINE RV	DUE N	255' (±20')

I-3

SET DNR MON & CED POST

6" MAPLE	N30°E	8.8'
8" W. OAK	S65°E	15.0'
7" R. OAK	S85°W	13.5'
RAND. S	DUE W	28'

SIGNED BY Carl F. Roser 04-06-82 DATE ____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ____ DATE ____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY ____ DATE ____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. ____ LAKE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET