LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 20 N., R. 12 W.	F-7; G-5; G-6
2. PROPERTY CONTROLLING IN SECTION 16	T. 20 N., R. 12 W.	14
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on June 26, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument and accessories and/or subsequent restoration:~~

C. (continued)

14

Set 1¼"x20" pipe

20" R. Pine	N45°W	101.7
15" Oak	S45°W	73.8

Set cedar post w/loc. tag

Due E	33'	
Center N-S rd. (gravel) Due W	6'	

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

F-7 Reestablished corner per standard B.L.M. instructions.

G-5 Recovered corner as 1"x18" pipe which fits F. Jones witness.

G-6 Restored corner per standard B.L.M. instructions.

14 Established corner per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-7			G-5			G-6		
Set DNR monument & cedar post			Found pipe, added DNR mon. & cedar post			Set DNR mon. & cedar post		
4" W. Pine	N32°E	31.9	4" W. Pine	N67°W	62.0	17" R. Pine	N03°E	49.5
12" R. Pine	S86°E	76.0	16" W. Pine	S75°E	70.3	15" R. Pine	S28°E	60.18
9" W. Pine	S40°E	53.1	14" R. Pine	Due S	76.8	16" R. Pine	N75°W	129.55
						USGS BM mon.	S21°W	124.64

SIGNED BY Carl F. Roser DATE 8/27/74

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (CHIEF OF SURVEY PARTY) DATE _____

APPROVED AND SIGNED BY _____ (MICHIGAN REGISTERED LAND SURVEYOR) DATE _____

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

NORTH NEWKIRK TOWNSHIP
LAKE COUNTY

Form No. ML M735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS