LAND CORNER RECORDATION CERTIFICATE

1. PUBLIC LAND SURVEY 20 T. 7 N. R. /2 E. 8-D 2. PROPERTY CONTROLL-20 ,T. 7 N. R. /2 E. 8-D 3. MISCELLANEOUS PROPERTY IN SECTION ,T. S., R. W. 4. LOT NO. , RECORDED PLAT	- LAPECR
A. LOT NO, RECORDED PLAT	_
A. MISCELLANEOUS PROPERTY IN SECTION, T S., R	_
o, PRIVATE CLAIMS	-
D. Scott do hereby certify that under requirements	
do hereby certify that under requirements	REGISTER OF DEEDS STAMP AN FILING NUMBER
the corner points mentioned in lines 1 and 2 above (identified with circles on in field survey on MARCH 15 19 22, established, re-established, monum restored as expressed below and in conformance with regulations and rules therefore survey instructions of the United States Department of the Interior, Bureau of Leontr of law. Furthermore, that the corner points mentioned in lines 3, 4 and 19 22, found, recovered, restored, established or re-established formance with the rules of the Michigan State Board of Registration for Land Survey.	dex code diagram — over) were, is ented, re-monumented, recovered re as required in the current man and Management or by a decree of d5 above were, in a field survey thed as expressed below and in co
law: A. Description of original monument and accessories and/or subsequent restoration	n.
	. 11. 12.
B. Description of corner evidence found and/or method applied in restoring or re-e	stablishing corner:
15" Iron Rod Witnesses Furnished by	Mich Wepi G.
-1- Higherbyes	
ate Highways.	
ate Highways.	
C. Description of monument for corner and accessories established to perpetuate	locating the position of the cor
	locating the position of the cor
C. Description of monument for corner and accessories established to perpetuate ## Tran Rod	locating the position of the cor
C. Description of monument for corner and accessories established to perpetuate ## Iron Rod	locating the position of the cor
C. Description of monument for corner and accessories established to perpetuate ## Iron Rod	locating the position of the cor
1/2" I RON Rod S. SS' E. 33.85' To A Light Pole S. 40' W. 37.77' To A Telephone Pole N. 15 W. 58.35 To A Telephone Pole	locating the position of the cor
C. Description of monument for corner and accessories established to perpetuate 12" I RON Rod S. 55° E. 33.85' To A Light Pole S. 40° W. 39.99' To A Telephone Pole N. 15 W. 58.35 To A Telephone Pole N. 50 E. 52.60 To A Sign Post	
C. Description of monument for corner and accessories established to perpetuate **Ron Rod** S. 55° E. 33.85' To A Light Polc S. 40° W. 39.99' To A Telephone Polc N. 15 W. 58.35 To A Telephone Polc N. 50 E. 52.60 To A Sign Post	locating the position of the con
C. Description of monument for corner and accessories established to perpetuate 12" I RON ROD S. SS' E. 33.85' To A Light Polc S. 40' W. 39.99' To A Telephone Polc N. 15 W. 58.35 To A Telephone Pole N. 50 E. 52.60 To A Sign Post SIGNED BY DATE	
C. Description of monument for corner and accessories established to perpetuate #2" I Ron Rod S. 55° E. 33.85' To A Light Polc S. 40° W. 30.90' To A Telephone Polc N. 15 W. 58.35 To A Telephone Polc N. 50 E. 52.60 To A Sign Post	3-15-12