

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

Luce County

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>45</u> N. S., R. <u>10</u> W.	D-9
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Buckler, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 11-2, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Sec. Cor. & 1/4 Cors. set by Wm. Ives, D.S. 1849. Bearings were:

D-9 1/4 Cor. bet. Sec's 20-29: Sugar 8, S66°W, 41 lks. and beech 5, N61°E, 19 lks.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:


D-9 Restored corner midway and on line bet. two Sec. corners. Found no evidence of original corner.

Note: this record replaces report filed 7-28-70. Correct corner is now 31.4' north and 6.8' east of the former monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-9 Placed 1" pipe w/4" alum cap at corner. New bearings:
8" maple, N10°E, 19.0' - 10" maple, S8°W, 11.7'-14" beech, N61°W, 18.6

SIGNED BY _____ DATE 3-20-80
Billy D. Buckler
 SURVEYOR'S MICHIGAN REGISTRATION NO. 8887



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____