STATE OF MICHIGAN DEPARTMENT OF NATURAL RESOURCES

LAND CORNER RECORD

			nce	COUNTY	
		Τ.	45N	R 11W	
DESCRIPTION OF CORNER	t corner bet. Secs. 16-2	1			
CORNER MONUMENT 5/81	iron buried in center of N	S road			
DATE MONUMENT PLACED	AND WITNESSED _4-16-69				
WITNESSES TO CORNER	8" Soft Maple (NBT) N40	% 41.1°	· · · · · · · · · · · · · · · · · · ·		
N	7" Soft Maple (NBT) S73	₩ 33.9°			
	AND				
CIRCLE CORNER REGIS	STERED	······································			

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

This corner re-witnessed as set by H. Lawrence, R.L.S. Found l_2^{ln} iron pipes set as witnesses, bearing, N45°E, 45.0° and S45°W, 45.0° Placed corner midway between these two pipes.

SURVEYOR'S SEAL

SIGNED

Willy V. Sucker,

Billy D. Buckler

ATF 5-2-69

DISTRIBUTION:

REGISTERED LAND SURVEYOR

County Courthouse Area Forester (Regions I & II) District or Region Surveyor Forestry Div., Lansing