

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

Luce Co.

Three Corners.

FOR CORNERS OF--	LOCATED IN--			CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. _____	N. _____ S. _____	R. _____	E. _____ W. _____	Cor. 4, Sec. 10 Cor. 1, Sec. 10 Cor. 11, Sec. 3
2. PROPERTY CONTROLLING IN SECTION	10 3	N. _____ S. _____	R. _____	E. _____ W. _____	
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____	N. _____ S. _____	R. _____	E. _____ W. _____	
4. LOT NO. _____	RECORDED PLAT _____				
5. PRIVATE CLAIMS _____					

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Euckler do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 6/18 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- Cor. 4, Sec. 10 N.W. 1/16 Corner, Section 10.
- Cor. 1, Sec. 10 West 1/16 Corner, bet. Secs. 3-10
- Cor. 11, Sec. 3 S.W. 1/16 Corner, Section 3.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- Cor. 4, Sec. 10 Corner placed at 1320.0' South of the West 1/16 Cor., bet. Secs. 3-10.
- Cor. 1, Sec. 10 Corner placed midway and on line bet. Sec. Cor. to West and $\frac{1}{4}$ Cor. to East.
- Cor. 11, Sec. 3 Corner placed 1320.0' North of the West 1/16 Cor. bet. Secs. 3-10.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Placed Dept. Markers at all corners.

- | | | | |
|-----------------|---------------|---------------------------------|---------------------------------|
| Cor. 4, Sec. 10 | New Bearings: | 10" Soft Maple N80°W 2.8' | 8" Soft Maple S62°E 15.9' |
| Cor. 1, Sec. 10 | New Bearings: | 13" Soft Maple S5°E 13.3' | 20" Y. Birch N7°E 42.9' |
| Cor. 11, Sec. 3 | New Bearings: | 8" Cedar N70°E 12.9' | 8" Tamarack S17°W 7.8' |

SIGNED BY: Billy D. Euckler

DATE: 6/27/73

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY: _____ CHIEF OF SURVEY PARTY

DATE _____

APPROVED AND SIGNED BY: _____

MICHIGAN REGISTERED LAND SURVEYOR

DATE _____

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Form No. MLM735
DOUGLASS BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS