LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:		1	
	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T S., R	E	
2. PROPERTY CONTROLL ING IN SECTION	32. ,T. 47. %, R. 10.	T. 5-Sec.32	
3. MISCELLANEOUS PROPERTY IN SECTION —	,T ^{N.} S., R	E	
4. LOT NO, RE	CORDED PLAT		•
5. PRIVATE CLAIMS	<u> </u>		REGISTER OF DEEDS STAMP AND FILING NUMBER
L Billy D. Buckler	do herel	by certify that under requirements	of P.A. 74, Michigan P.A. of 1970,
re-established, monumented, and rules therefore as required Bureau of Land Management and 5 above were, in a field su	re-monumented, recovered of d in the current manual of a or by a decree of a court of rivey on	or restored as expressed below as nurvey instructions of the United law. Furthermore, that the corr , 19, found, recovered, re	, 1978, established, and in conformance with regulations. States Department of the Interior, her points mentioned in lines 3, 4 estored, established or re-established stration for Land Surveyors or, by a
A. Description of original mo	nument and accessories and	or subsequent restoration:	
Sec.32 North 1/16 Corne			
•			
_			
•			
•			
•			
•			
B. Description of corner evide	ence found and/or method a	applied in restoring or re-establish	ing corner:
-		applied in restoring or re-establish	
-		•	ing corner:
-		•	
-		•	
-		•	
-		•	
-		•	
-		•	
Sec.32 Placed North 1/	16 corner midway bet	. 1/4 corner to North a	and Center cor. to South.
Sec.32 Placed North 1/	16 corner midway bet	•	and Center cor. to South.
Sec.32 Placed North 1/	16 corner midway bet	. 1/4 corner to North a	and Center cor. to South.
Sec.32 Placed North 1/	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	and Center cor. to South.
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88°	16 corner midway bet for corner and accessories es with 4" aluminum cap	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
Sec.32 Placed North 1/2 C. Description of monument Sec.32 Placed 1 pipe 1	for corner and accessories envith 4" aluminum car	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88°	for corner and accessories eswith 4" aluminum cap N, 68.2!, & 6" Ma	stablished to perpetuate locating to at corner. Bearings a	the position of the corner:
C. Description of monument Sec. 32 Placed 1" pipe v 8" Maple, N88° SIGNED BY Billy D	for corner and accessories eswith 4" aluminum cap N, 68.2!, & 6" Ma	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88°v	for corner and accessories envith 4" aluminum cap N, 68.2!, & 6" Ma Buckler EGISTRATION NO. 8	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88° SIGNED BY Billy D. SURVEYOR'S MICHIGAN R FOR STATE AND UNITED	for corner and accessories envith 4" aluminum cap N, 68.2!, & 6" Ma Buckler EGISTRATION NO. 8	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88° SIGNED BY	for corner and accessories envith 4" aluminum cap N, 68.2!, & 6" Ma Buckler EGISTRATION NO. 8	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:
C. Description of monument Sec.32 Placed 1" pipe v 8" Maple, N88° SIGNED BY Billy D. SURVEYOR'S MICHIGAN R FOR STATE AND UNITED	for corner and accessories eswith 4" aluminum cap V, 68.2!, & 6" Ma ABuckler EGISTRATION NO STATES AGENCIES:	stablished to perpetuate locating to at corner. Bearings and ple, S62 W, 51.3 & 1	the position of the corner:

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1978